



# Manure / Universal spreader **BE 1201-1401**



**stautmann**

The successful BE spreader range is complemented by two new models with large volumes for the professional farmer. Stable spreader units with a high distribution precision combined with galvanized body and frame ensure high operational readiness and a long lifetime. The four beater and the two disc spreader units are checked and approved by the DLG (Deutsche Landwirtschafts-Gesellschaft / German Agricultural Society).

# More output with proven spreading technology



## 1. Two beater spreader unit

The BE 1201 and BE 1401 are equipped with a robust two beater spreader unit with a 1.25 m wide passage. The aggressive beaters breakup the manure and spread it out evenly.



## 5. Hot-dip galvanised full steel body

The galvanised body and frame of the BE 1201 and BE 1401 lead to a low weight of the spreader and ensure a long lifetime because of the protection against corrosion.



## 2. Four beater spreader unit

The BE 1201 and BE 1401 can be equipped optionally with a four beater spreader unit. Because of the fan-shaped tines distribution widths of 6 – 8 m are reached.



## 3. Two disc spreading unit

High distribution widths are realized with the two beater spreading unit. The aggressive beaters breakup the manure and deliver it to the discs. The adjustable throwing blades enable distribution widths of up to 21 m.



## 4. Transport floor

The BE 1201 and BE 1401 are equipped with four 13 mm thick chains for the transport floor. The chains lie stable on the ground and can therefore reliably deliver crumbly and corned goods like lime to the spreading unit.



## 6. Plastic floor

The floor is made of weather-proof and shockproof plastic planks. These have very good glide capacities and ensure an effective transport of all goods.



### 7. Single or tandem axle

The BE 1201 can be equipped with a single axle as well as with a tandem axle. The BE 1401 is available only with tandem axle, but can be equipped with a steering axle as option.



### 8. Hydraulic slurry door

For the precise distribution of fine-grain material, all spreader units can be combined with a hydraulic slurry door.



### 9. Display for the slurry door

The hydraulic slurry door includes a display at the front wall for the current position of the sludge board.



### 10. Adjustment of the tail gate

The channel between the top of the discs vanes and the rear protection hood can be adjusted to suit the needs of the spreading material. A boundary spread limiter is also available as option.



### 11. Control

All functions of the BE 1201 and BE 1401 are controlled with the tractor valve as standard. The oil flow diverter for the stageless adjustment of the transport floor can be easily reached from the tractor. As option the control with electrohydraulic is also possible.



### 12. Shock absorbers

The BE 1201 and BE 1401 are equipped with a spring-loaded drawbar. Shocks and vibrations, especially when the spreader is loaded, are very well absorbed. This leads to a significant increase of the driving comfort.

## Manure / Universal spreaders BE 1201 / BE 1401

Type		BE 1201 2-beaters	BE 1201 4-beaters	BE 1201 2-discs	BE 1401 2-beaters	BE 1401 4-beaters	BE 1401 2-discs
Perm. total weight							
High drawbar	kg	12000	12000	12000	14000	14000	14000
low drawbar	kg	13000	13000	13000	15000	15000	15.000
Own weight „(two axles)“	kg	4250	4400	4900	4550	4700	5200
Total dimensions							
L x B x H	m	7.58x2.36x3.30	7.62x2.36x3.30	8.05x2.36x3.30	7.58x2.51x3.30	7.62x2.51x3.30	8.05x2.51x3.30
Interior dimensions							
Lengths to sludge board	m	4.92	4.92	4.92	4.92	4.92	4.92
Lengths to spr. unit 2 beaters	m	5.32	-	5.32	5.32	-	5.32
Lengths to spr. unit 4 beaters	m	-	5.32	-	-	5.32	-
Width	m	1.80	1.80	1.80	1.80	1.80	1.80
Height with guard strip (30mm)	m	0.95	0.95	0.95	0.95	0.95	0.95
Loading height	m	2.33	2.33	2.33	2.33	2.33	2.33
Distrib. mech. passage	m	1.25	1.25	1.25	1.25	1.25	1.25
Distrib. width sludge board	m	1.12	1.12	1.12	1.12	1.12	1.12
Capacity							
to sludge board	m <sup>3</sup>	10.20	10.20	10.20	10.20	10.20	10.20
to 2 beaters	m <sup>3</sup>	12.00	-	12.00	12.00	-	12.00
to 4 beaters	m <sup>3</sup>	-	12.00	-	-	12.00	-
Power requirement	KW	74	74	74	74	74	74
	HP	100	100	100	100	100	100
Dimensions with tires		560/45 R 22,5	560/45 R 22,5	560/45 R 22,5	560/45 R 22,5	560/45 R 22,5	560/45 R 22,5

All diagrams, technical data and weights are subject to change by way of ongoing technical development of our products and are therefore not binding for delivery.

**Program**  
**STRAUTMANN**



2000/R. 0411



**STRAUTMANN**

B. Strautmann & Söhne GmbH u. Co. KG • Bielefelder Straße 53 • D-49196 Bad Laer  
Tel. +49(0)54 24/8 02-0 • Fax +49(0)54 24/8 0276  
kontakt@strautmann.com • www.strautmann.com