



SPECIFICATIONS		OUTLANDER MAX 650 EFI
ENGINE	Type	649.6cc, V-twin, liquid-cooled, SOHC, 8-valve (4-valve/cyl)
	Bore & Stroke	82 x 62 mm
	Net Power	< 15kW (EC version only)
	Carburetion/EFI	46 mm Throttle Body, Siemens [®] VDO injector
	Starting System	Electric
CHASSIS	Transmission	CVT, sub-transmission with high, low, park, neutral & reverse Standard engine braking
	Drive Train	Selectable 2w/4w shaft driven with Visco-lok [†] front differential
	CO Emissions	Euro-2 approved
	Frame	SST™
	Front Suspension Type/Shocks	Double A-arm
DIMENSIONS	Front Suspension Travel	203 mm (8 in)
	Rear Suspension Type/Shocks	TTI independent
	Rear Suspension Travel	229 mm (9 in)
	Front Brake	2 inboard hydraulic discs
	Rear Brake	1 inboard hydraulic disc
	Tyres/Front	660 x 203 x 305 mm 26 x 8 x 12 in
	Tyres/Rear	660 x 254 x 305 mm 26 x 10 x 12 in
	Wheels	12" Cast wheels
	L x W x H (mm)	2,387 x 1,168 x 1,143 mm
	L x W x H (in)	94 x 46 x 45 in
FEATURES	Wheelbase	1,499 mm (59 in)
	Seat Height	877 mm (34.5 in)
	Ground Clearance	305 mm (12 in)
	Dry Weight	326 kg (719 lbs)
	Towing Capacity	590 kg (1,300 lbs)
	Rack Capacity	Front: 45 kg (100 lbs) Rear: 90 kg (200 lbs)
	Storage	Rear storage 20L CRS (Convertible Rack System)
	Fuel Capacity	16.3L
	Instrumentation	Multi-function digital LCD gauge: Speedometer, tachometer (bar graph RPM, bottom bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4x4 indicator, temperature and engine lights, fuel gauge, auto shut off after 15 minutes
	Anti-Theft System	D.E.S.S. (Digital Encoded Security System)
AVAILABLE PACKAGES	Electrical	Prewired for winch
	Lighting	2 fender mounted headlamps (35W) with tail light/brake light
	DC Outlet	Lighter type in console, standard connector in the back (15A)
	Warning Signal	Horn
	Colour Available	Viper Red
XT Package Content	New dual-mode Dynamic Power Steering (DPS) New Visco-Lok QE, New 12" cast aluminum wheels New 650 watts magneto BRP XL3000 winch with roller fairlead and wired remote controls, Aggressive Carlisle [®] ACT Radial tyres, Heavy-duty front & rear bumpers, Handlebar wind deflectors	
Colour Available for XT	Yellow	



Outlander MAX 650 EFI



Outlander MAX 650 EFI XT™

■ EC versions features

© 2009 Bombardier Recreational Products Inc (BRP). All rights reserved. ®, ™ and the BRP logo are registered trademarks of Bombardier Recreational Products Inc. or its affiliates. †Visco-Lok is a trademark of GKN Viscodrive GmbH. ‡All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol/drugs don't mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. Respect the minimum age as required by law. Never carry passengers on any ATV not specifically designated for such use. Can-Am Outlander MAX ATVs: BRP recommends not to carry any passengers under the age of 12.