







	SPECIFICATIONS	RENEGADE 500 EFI	RENEGADE 800R EFI	
ENGINE	Type	499.6cc, V-twin, liquid-cooled, SOHC, 8-valve (4-valve/cyl)	799.9cc, V-twin, liquid-cooled, SOHC, 8-valve (4-valve/cyl)	 <p>Renegade 500 EFI</p>
	Bore & Stroke	82 x 47 mm	91 x 62 mm	
	Net Power	< 15kW (EC version only)	< 15kW (EC version only)	
	Carburetion/EFI	46 mm Throttle Body, Siemens' VDO injectors	46 mm Throttle Body, 2 Siemens' VDO injectors	 <p>Renegade 800R EFI</p>
Starting System	Electric	Electric		
Transmission	CVT, sub-transmission with high, low, park, neutral & reverse Standard engine braking	CVT, sub-transmission with high, low, park, neutral & reverse Standard engine braking		
Drive Train	Selectable 2w/4w shaft driven with Visco-lok ¹ front differential	Selectable 2w/4w shaft driven with Visco-lok ¹ front differential		
	CO Emissions	Euro-2 approved	Euro-2 approved	
CHASSIS	Frame	SST™	SST™	 <p>Renegade 800R EFI X xc</p>
	Front Suspension Type/Shocks	RS-Type Double A-arm, forged aluminum upper arm/Motion Control shocks	RS-Type Double A-arm, forged aluminum upper arm/HPG shocks	
	Front Suspension Travel	216 mm (8.5 in)	216 mm (8.5 in)	
	Rear Suspension Type/Shocks	RS-Type TTI™ independent/Motion Control shocks	RS-Type TTI™ independent/HPG shocks	
	Rear Suspension Travel	229 mm (9 in)	229 mm (9 in)	
	Front Brake	2 hydraulic discs	2 hydraulic discs	
	Rear Brake	1 inboard hydraulic disc	1 inboard hydraulic disc	
	Tyres/Front	ITP ² Holeshot ³ ATR 635 x 203 x 305 mm 25 x 8 x 12 in	ITP ² Holeshot ³ ATR 635 x 203 x 305 mm 25 x 8 x 12 in	
	Tyres/Rear	ITP Holeshot ATR 635 x 254 x 305 mm 25 x 10 x 12 in	ITP Holeshot ATR 635 x 254 x 305 mm 25 x 10 x 12 in	
	Wheels	Center cast aluminum	Center Cast Aluminum with reinforcement ring	
DIMENSIONS	L x W x H (mm)	2,184 x 1,168 x 1,143 mm	2,184 x 1,168 x 1,143 mm	 <p>Renegade 800R EFI X xc</p>
	L x W x H (in)	86 x 46 x 45 in	86 x 46 x 45 in	
	Wheelbase	1,295 mm (51 in)	1,295 mm (51 in)	
	Seat Height	877 mm (34.5 in)	877 mm (34.5 in)	
	Ground Clearance	279 mm (11 in)	279 mm (11 in)	
	Dry Weight	279 kg (614 lbs)	279 kg (614 lbs)	
	Towing Capacity	590 kg (1,300 lbs)	590 kg (1,300 lbs)	
	Rack Capacity	16 kg (35 lbs)	16 kg (35 lbs)	
	Storage	Rear storage 3.7L	Rear storage 3.7L	
	Fuel Capacity	16.3L	16.3L	
FEATURES	Instrumentation	Multi-function gauge: Speedometer, tachometer, odometer, trip and hourmeters, fuel, gear position, 4x4 indicator, diagnostics, auto shut off	Multi-function gauge: Speedometer, tachometer, odometer, trip and hourmeters, fuel, gear position, 4x4 indicator, diagnostics, auto shut off	 <p>Renegade 800R EFI X xc</p>
	Anti-Theft System	D.E.S.S. (Digital Encoded Security System)	D.E.S.S. (Digital Encoded Security System)	
	Electrical	Prewired for winch	Prewired for winch	
	Lighting	4 fender mounted Projector Beam headlamps (60W) with tail light/brake light	4 fender mounted Projector Beam headlamps (60W) with tail light/brake light	
	DC Outlet	Lighter type in console, standard connector in the back (15A)	Lighter type in console, standard connector in the back (15A)	
	Warning Signal	Horn	Horn	
AVAILABLE PACKAGES	Colour Available	Viper Red	Viper Red	 <p>Renegade 800R EFI X xc</p>
	X xc Package Content		New dual-mode Dynamic Power Steering (DPS), new Visco-Lok QE, new full aluminium Beadlock wheels with inner reinforcement rings, new front sway bar, new 650 watts magneto, front KYB HPG aluminum piggyback shocks with dual speed compression, rebound and preload adjustments, rear KYB HPG with remote reservoir shocks with dual speed compression, rebound and preload adjustments, aluminum skid plate, handlebar wind deflectors, aluminum taper-profile handlebar with square pad, new X package graphics, new X package seat cover	
	Colour Available for X xc		Yellow & black with X package graphics	

■ EC versions features

■ EC versions features

© 2009 Bombardier Recreational Products Inc (BRP). All rights reserved. ®, ™ and the BRP logo are registered trademarks of Bombardier Recreational Products Inc. or its affiliates. ¹Visco-Lok is a trademark of GKN Viscodrive GmbH. ²All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at any time to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol/drugs don't mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. Respect the minimum age as required by law. Never carry passengers on any ATV not specifically designated for such use. Can-Am Outlander MAX ATVs: BRP recommends not to carry any passengers under the age of 12.