

**COUNTRYLINE**



**COUNTRYLINE EQUIPMENT**

TRACTOR MOUNTED ATTACHMENTS FOR THE  
AGRICULTURAL, SMALLHOLDER AND  
EQUESTRIAN MARKETS

*When only the best will do...*





**MANUFACTURING  
EXCELLENCE  
SINCE 1962**

Since 1962 the Wessex name has been synonymous with superb quality, British built machines for the agricultural and groundcare markets. Our equipment is built for demanding applications, where reliability and durability are paramount.

**WESSEX INTERNATIONAL'S** global distribution network has distributors and dealerships in many countries. Whatever Wessex product you invest in, you can be sure of support from your local dealer right through the machines lifetime, backed by Wessex International's commitment to excellent customer service.

Our friendly and knowledgeable staff are here to advise you on the best equipment for your application. We are convinced you will find our machinery beneficial to your organisation both in terms of user satisfaction and economic ownership.




**CHARLES BROWNING**

Managing director



**1962**

In the heart of rural Hampshire, Wessex began manufacturing grass cutting and forage equipment.



**1970's**

Wessex were the first to manufacture a range of scaled down implements to suit the new compact tractor from Japan.



**1980's**

Wessex increased their focus on equipment to meet the needs of landscapers and grounds maintenance contractors.



**1990's**

As ATVs started to grow in popularity, Wessex produced a line-up of attachments to suit.



**2003**

Broadwood International was established as the distributor of quality equipment including the well-known SnowEx salt spreaders & SweepEx push brooms.



**2008**

Broadwood International acquired Wessex Machinery – now a leading manufacturer of professional grounds maintenance machinery.



**2014**

In line with the increased focus on global distribution of the Wessex product range, the company has been renamed Wessex International. This coincides with relocation to the current 50,000sqft factory in Andover, Hampshire.



**"FOR THE PRIVATE ESTATE, SMALLHOLDER & EQUESTRIAN MARKETS"**

<b>CM SERIES FINISHING MOWERS</b>	4	<b>STX SERIES PADDOCK CLEANERS</b>	21
CM-150, 1.5m, CM-180, 1.8m		STX-120 1.2m, STX-180, 1.8m	
<b>SCRUBMASTER ROTARY SLASHER</b>	5	<b>STC SERIES COLLECTORS</b>	22-23
SM-66, 1.7m		STC-120 1.2m, STC-180, 1.8m	
<b>WFM SERIES FLAIL MOWERS</b>	6	<b>HYDRAULIC TIPPING TRAILERS</b>	24
WFM-145, 1.45m, WFM-160, 1.60m, WFM-175, 1.75m, WFM-205, 2.05m, WFM-220, 2.25m		T-125, 1.5ton, 1.5T-LGPW, 1.5ton, 3.0T-LGPW, 3.0ton	
<b>WFMHD SERIES FLAIL MOWERS</b>	7	<b>MOUNTED FERTILIZER SPREADERS</b>	25
WFM-200HD, 2.00m, WFM-225HD, 2.25m		FS-270, FS-360	
<b>ZME VERGE &amp; BANK MOWERS</b>	8-9	<b>TRAILED FERTILIZER SPREADERS</b>	26
ZME-125, 1.25m, ZME-155, 1.55m		FS-170T, FS-270T	
<b>ZMTE / ZLE VERGE MOWERS</b>	10-11	<b>BENEFITS OF A BROOMEX PUSH BROOM</b>	27
ZMTE-1600, 1.64m, ZMTE-1800, 1.84m, ZMTE-2000, 2.04m, ZLE-1600, 1.6m, ZLE-1800, 1.8m, ZLE-2000, 2.0m		<b>BROOMEX C-BROOM</b>	28
<b>LANDMASTER ROTARY CULTIVATOR</b>	12	BM-150 MAX, BM-180 MAX, BM-240 MAX	
RC-120, 1.2m, RC-150, 1.5m		<b>BROOMEX BM PUSH BROOMS</b>	30
<b>CHT HEDGE CUTTERS</b>	13	BM-150, BM-180, BM-240	
CHT-120, 1.2m, CHT-150, 1.5m, CHT-200, 2.0m		<b>BROOMEX BP PUSH BROOMS</b>	31
<b>T320A/T350S HEDGE CUTTERS</b>	14-15	BP-150, BP-180, BP-240	
T320A, 3.2m, T350S, 3.6m		<b>BROOMEX APPLICATIONS</b>	32
<b>T380D/T430D HEDGE CUTTERS</b>	16-17	<b>LS-100 HYDRAULIC LOG SPLITTERS</b>	34
T380D, 3.9m, T430D, 4.3m		LS-100, HLS-100	
<b>T500G / TPE600 HEDGE CUTTERS</b>	18-19	<b>AFTER-SALES SERVICE</b>	35
T500G, 5m, TPE600, 6m			
<b>MTC/X COLLECTORS</b>	20		
MTX120, 1.2m, MTC120, 1.2m			

*When only the best will do...*



3 overlapping rotors means 100% blade coverage

Reliable belt drive

Simple height adjustment

Optional mulching blade



The **WESSEX CM SERIES FINISHING MOWERS** feature 4 wheels for a high level of manoeuvrability and will leave a premium finish on estate lawns and fine turf.

3 overlapping rotors prevent unsightly uncut strips while the wheels are easily adjusted to the perfect height. These mowers are available in 2 working widths, and are well suited to compact tractors from 15hp.

<b>W SPECIFICATIONS</b>	<b>CM-150</b>	<b>CM-180</b>
Working width	1.5m	1.8m
Overall width	1.62m	1.93m
Cutting height range	20-110mm	20-110mm
Weight	196kg	214kg
Minimum power required	15hp	20hp



## KEY FEATURES & BENEFITS

**OVERLAPPING ROTORS** – No uncut strips of grass

**ADJUSTABLE LOWER LINK POINTS** – Will suit any compact tractor

**SIMPLE BELT ADJUSTMENT** – Ease of maintenance

**FLOATING TOP LINK POINT** – Accurate ground contour following

**SIMPLE CUTTING HEIGHT ADJUSTMENT** – Ease of operation

**OPTIONAL MULCHING BLADES** – Lacerates clippings enhancing decomposition



**WESSEX ARE STILL  
SUPPLYING PARTS FOR  
SCRUBMASTERS  
SOLD IN THE 1960'S!**

In short, the **WESSEX SCRUBMASTER ROTARY SLASHER** is unstoppable! Built to cope with the most arduous applications, this robust machine is ideal for controlling areas of dense vegetation and heavy scrubland ie, forestry plantations, firebreaks, rides, and gorse moorlands etc.

The massive blades will deliver over 3,000 1 ton impact cuts per minute making light work of brambles, gorse, heather and trees / saplings up to 100mm diameter. The chain cutters are recommended in areas where there are likely to be hidden rocks, boulders and tree stumps etc. The chains will thoroughly lacerate cut material, accelerating the breakdown and rotting process.



SCAN  
TO SEE  
A DEMO  
SCRUBMASTER



## KEY FEATURES & BENEFITS

- HEAVY-DUTY CONSTRUCTION** – Durability
- MASSIVE GEARBOX** – Maximum drive transmission
- FRICTION PLATE CLUTCH** – Overload protection
- BLADE OR CHAIN CUTTERS ARE INTERCHANGEABLE** – Varying applications
- REPLACEABLE SKID SHOES** – Ease of maintenance
- FLOATING HEADSTOCK** – Follows ground contours in rough areas
- ADJUSTABLE SIDE SKIDS** – Simple height adjustment



## SPECIFICATIONS SM-66

Working width	1.7m
Overall width	1.8m
Blade tip speed	70.7 m/s
Weight (blades & chains)	516kg blades 468kg chains
Minimum power required	45hp



**KEY FEATURES & BENEFITS**

- FOR TRACTORS UP TO 60HP**
- MANUAL SIDES SHIFT (WFM-130),  
HYDRAULIC SIDE SHIFT (WFM-145, 160,  
175, 205 & 220)**
- CENTRAL GEARBOX EQUIPPED WITH  
FREE WHEEL CLUTCH**
- FULL WIDTH ADJUSTABLE REAR ROLLER**
- CE SAFETY CERTIFIED**
- ADJUSTABLE SIDE SKIDS**
- CAT 1, 3-PT HITCH**
- HAMMER OR Y-PATTERN FLAILS**

For control of dense vegetation, long grass and woodland rides, the **WESSEX WFM FLAIL MOWERS** are a real tough performer and are perfectly suited to the job. Hammer or Y-pattern flails pulverise tough material while a full width adjustable rear roller maintains an even cutting height.

These machines can be used in-line or offset (excluding WFM-115), and are available to suit compact tractors from 20hp. The Wessex WFM flail mower is the machine of choice for the discerning smallholder!

<b>SPECIFICATIONS</b>	<b>WFM-115</b>	<b>WFM-130</b>	<b>WFM-145</b>	<b>WFM-160</b>	<b>WFM-175</b>	<b>WFM-205</b>	<b>WFM-220</b>
<b>Working width</b>	1.15m	1.30m	1.45m	1.60m	1.75m	2.05m	2.25m
<b>Weight</b>	325kg	335kg	385kg	405kg	425kg	495kg	530kg
<b>Tractor horsepower</b>	20hp	25hp	25hp	30hp	40hp	55hp	60hp
<b>No. of hammers</b>	14	16	18	20	22	26	28
<b>No. of belts</b>	4	4	4	4	4	4	4



Sharing the same build quality as the smaller flails, the **WESSEX HD SERIES** with hammer flails is suited to tractors from 50hp. Ideal for general farm work, small contractors and Councils.

**KEY FEATURES & BENEFITS**

- FOR TRACTORS FROM 50-100HP**
- HYDRAULIC SIDE SHIFT**
- CENTRAL GEARBOX EQUIPPED WITH FREE WHEEL CLUTCH**
- FULL WIDTH ADJUSTABLE REAR ROLLER**
- CE SAFETY CERTIFIED**
- ADJUSTABLE SIDE SKIDS**
- CAT 2, 3-PT HITCH**
- HAMMER FLAILS**
- DOUBLE SKIN DECK**
- LOW MAINTENANCE**
- DRIVE BELTS ACT AS SHOCK OVERLOAD PROTECTION**

<b>SPECIFICATIONS</b>	<b>WFM-200HD</b>	<b>WFM-225HD</b>
Working width	1.98m	2.25m
Weight	750kg	810kg
Tractor horsepower	50-100hp	50-100hp
No. of hammers	20	20
No. of belts	4	5

*When only the best will do...*

# **ZME-125/ZME-155** OFFSET VERGE & BANK **MOWERS**



**SCAN  
TO SEE  
VERGE  
MOWERS**



Designed specifically for use with smaller tractors from 20hp, the **WESSEX ZME-125** and **ZME-155** are two offset verge and bank mowers, which are ideal for use with private estates, large gardens and smallholdings.

The ZME machines are highly manoeuvrable and can be used as an in-line flail mower behind the tractor, or fully offset to the right, with a cutting angle between -50 and +90 degrees of horizontal. This means that verges, banks, ditches or even the side of a low hedge can be maintained with a single machine.



## **KEY FEATURES**

**IDEAL FOR COMPACT TRACTORS**

**TOP MOUNTED GEARBOX**

**PIVOTING ARM ON SELF-LUBE BEARING**

**MECHANICAL BREAK-AWAY**

**FRONT AND REAR GUARDS**

**ADJUSTABLE REAR ROLLER**


**INTEGRAL ROLLER BEARINGS**

**CABLE CONTROLS**

**-50 DEG TO + 90 DEG CUTTING ANGLE**



The arms rotating pivot has a self-lubricating bearing for minimal maintenance.



Mechanical breakaway.



The rotor bearings are integral for maximum protection from damage.




The ZME comes standard with simple cable controls



Y-pattern flails are fitted as standard.

## WORKING POSITIONS



## KEY

	ZME-125	ZME-155
A	1.25m	1.55m
B	1.11m	1.12m
C	0.70m	0.70m
D	1.74m	2.04m
E	1.54m	1.54m
F	1.30m	1.30m
G	0.60m	0.60m
H	0.75m	0.75m

## SPECIFICATIONS

	ZME-125	ZME-155
Cutting width	1.25m	1.55m
Flail head angle	+90 to -50°	+90 to -50°
Blade tip speed	45m/sec	45m/sec
Weight	232kg	261kg
Tractor horsepower	18-30hp	25-40hp
Min tractor weight	700kg	900kg
Min tractor width	1.1m	1.2m



SCAN  
TO SEE  
**VERGE**  
MOWERS



The **WESSEX ZMTE** is a popular general purpose verge mower in 3 working widths from 1.6m to 2.0m. Ideal for use on estates and within the agricultural market sector, the ZMTE features a side mounted gearbox, adjustable rear roller, the option of a hydraulic break-away device and the choice of Y-pattern or hammer flails.

All models cut to the right hand side of the tractor, whilst the ZMTE-2000 is also available as a left handed version for use on the UK highway.

The ZLE heavy-duty verge mowers carry similar characteristics to the ZMTE range, but are designed for more arduous applications and contractual use. The ZLE also has a double skin deck, a larger diameter roller and heavier hammer flails with a high tip speed.




## KEY FEATURES

### **ZMTE**

- FLOATING FRAME - FOR UNDULATING GROUND**
- SIDE MOUNTED - GEAR BOX**
- Y FLAILS OR HAMMER FLAILS**
- 45 DEG TO + 90 DEG - CUTTING ANGLE**
- OPTIONAL - HYDRAULIC BREAK-AWAY**
- FRONT STONE GUARDS**
- ADJUSTABLE - REAR GUARDS**
- INTEGRAL ROLLER - BEARINGS**
- CABLE CONTROLS**
- LOCKING TRANSPORT POSITION**
- PIVOTING ARM - ON SELF-LUBE BEARING**

### **ZLE**

- DOUBLE SKIN DECK**
- SIDE MOUNTED - GEARBOX**
- HEAVY-DUTY HAMMER FLAILS**
- HIGH BLADE TIP SPEED**
- HYDRAULIC BLOCK VALVE - LOCKS MACHINE FOR TRANSPORT**
- 60 DEG TO +90 DEG - CUTTING ANGLE**
- MECHANICAL BREAK-AWAY**
- SELF-LUBRICATING BEARINGS - ON LINKAGE**
- FRONT AND REAR - GUARDS**
- HEAT TREATED PINS**
- HEIGHT ADJUSTABLE ROLLER**
- COUNTER KNIFE**



The dynamically balanced rotor has the blades situated in a spiral pattern for smooth operation.



Simple height adjustment is achieved by altering the rear roller.




The floating A-frame allows the machine to operate in undulating conditions.



The ZMTE features Y-pattern flails as standard, with the option of hammers, whilst the ZLE has hammers as standard.

## WORKING POSITIONS



## KEY

	ZMTE 1600	ZMTE 1800	ZMTE 2000	ZLE 1600	ZLE 1800	ZLE 2000
A	2.8m	3.0m	3.2m	2.8m	3.0m	3.2m
B	1.92m	1.97m	1.97m	1.92m	1.92m	1.92m
C	1.64m	1.84m	2.04m	1.6m	1.8m	2.0m
D	0.22m	0.22m	0.22m	0.57m	0.57m	0.57m
E	1.8m	1.86m	1.86m	1.8m	1.8m	1.8m

## SPECIFICATIONS

	ZMTE 1600	ZMTE 1800	ZMTE 2000	ZLE 1600	ZLE 1800	ZLE 2000
Cutting width	1.64m	1.84m	2.04m	1.6m	1.8m	2.0m
Max side-shift	2.8m	3.0m	3.2m	2.8m	3.0m	3.2m
Flail head angle	45°/90°	45°/90°	45°/90°	60°/90°	60°/90°	60°/90°
Blade tip speed	46m/sec	50m/sec	50m/sec	53m/sec	53m/sec	53m/sec
Weight	532kg	610kg	636kg	665kg	695kg	725kg
Tractor horsepower (hp)	50-80	60-80	70-80	50-100	60-100	70-100
Min tractor weight	2200kg	2400kg	2600kg	2400kg	2600kg	2800kg
Min tractor width	1.8m	2.0m	2.2m	1.8m	2.0m	2.2m



Create the perfect seed bed or vegetable garden with a **WESSEX LANDMASTER ROTARY CULTIVATOR**. Available in 1.2 and 1.5m working widths, they are ideal for nurseries and glasshouses as well as private gardens, and boast features found on much more expensive models, such as slip clutch, adjustable tailgate and adjustable side depth skids.

Coupled to a compact tractor from 20hp+, the Wessex Landmaster rotary cultivator also meets all UK guarding regulations, for peace of mind.



SCAN  
TO SEE  
**LANDMASTER  
ROTARY  
CULTIVATOR**



## KEY FEATURES & BENEFITS

**HEAVY CAST GEARBOX  
CHAIN & SPROCKET DRIVE  
ADJUSTABLE SIDE SKIDS  
ADJUSTABLE TAILGATE  
CE CERTIFIED  
AVAILABLE IN 1.2 AND 1.5M  
WORKING WIDTHS**

## SPECIFICATIONS **RC-120** **RC-150**

Working width	1200mm	1500mm
Overall width	1340mm	1645mm
No. of blades	36	42
Weight	180kg	200kg
Minimum power required	20hp	25hp



**WESSEX CHT HEDGE CUTTERS**

are perfect for trimming small trees, hedges and pruning edges, and are ideal for compact tractors of 15hp and above. All models feature a cutter bar and are available with either cable or joystick controls. They are powered from the tractor hydraulic, or an optional hydraulic power pack is available.

**W SPECIFICATIONS**

	<b>CHT-120</b>	<b>CHT-150</b>	<b>CHT-200</b>
<b>Cutter bar size</b>	120cm	150cm	200cm
<b>Vertical reach</b>	410cm	550cm	600cm
<b>Horizontal height</b>	260cm	380cm	380cm
<b>Horsepower required</b>	15 - 40hp	25 - 50hp	30 - 60hp
<b>Oil flow (L/min)</b>	12	20	25
<b>Weight</b>	180kg	200kg	220kg
<b>Minimum tractor weight</b>	500kg	600kg	700kg



SCAN TO SEE CHT HEDGE CUTTERS



*When only the best will do...*

MODEL  
SHOWN  
T350S  
(INSET)



The **WESSEX 320A & T350S HEDGE CUTTERS** are designed to suit compact tractors from 15hp.

Both hedge cutters are ideal for use on private estates, in large gardens, or on the public highway, and the T530S can work on either the left or right hand side of the tractor.



SCAN  
TO SEE  
T320A  
HEDGE  
CUTTERS



Cable controls



Mono lever electric controls



Y-pattern flails are fitted as standard.



## KEY FEATURES & BENEFITS

**FLOATING FLAIL HEAD / CUTTER BAR T350S**

**REVERSIBLE ROTOR**

**Y FLAILS**

**MECHANICAL BREAKAWAY**

**FRONT GUARD ON FLAIL HEAD**

**ADJUSTABLE REAR ROLLER**

**CHOICE OF CABLE OR MONO-LEVER  
ELECTRIC CONTROLS**

**OIL COOLER WITH THERMOSTAT**

**FULLY INDEPENDENT HYDRAULICS**

**MECHANICAL ROLL OVER PROTECTION  
SYSTEM**

**FOR USE WITH TRACTORS FROM 25HP**


# WESSEX T320A/T350S HEDGE CUTTERS



Floating head allows the machine to give an even cut over uneven ground.



Front steel guards eliminates projectiles being thrown out in work.



Adjustable rear roller - simple cutting height setting.



Tractor stabilizers maintain rigidity on the tractor.





Optional cutter bar, ideal for use on public footpaths etc – supplied as standard on T530S and optional on T320A



Mechanical breakaway.

## WORKING POSITIONS T320A



## FLAT HEAD MODEL

A	1.505m
B	0.695m
C	1.94m

## KEY T320A T350S

## T320A T350S

A	3.22m	3.62m	G	1.60m	4.66m
B	1.84m	1.87m	H	2.76m	3.31m
C	0.93m	1.40m	I	1.10m	1.10m
D	2.05m	2.17m	M	0.62m	1.52m
E	3.61m	4.97m	N	0.30m	0.30m
F	1.10m	1.31m			

## SPECIFICATIONS T320A T350S

Cutting width	0.8m	1.50m
Number of flails	32 Y-pattern	n/a
Max horizontal reach	3.22m	3.62m
Flail head angle	190°	n/a
Rotor speed	3,200rpm	–
Blade tip speed	48m/sec	n/a
Max motor power	29hp	–
Max power to the rotor	20hp	–
Oil tank capacity	60L	n/a
Weight	370kg	230kg
Tractor horsepower	25-40hp	15-50hp
Min tractor weight	900kg	700kg
Min tractor width	1.2m	1.0m
Category linkage	1 & 2	1 & 2

# **T380D/T430D** WESSEX **HEDGE CUTTERS**



**MACHINE AVAILABLE WITH REAR OR TOP MOUNTED CUTTING HEADS**

The **WESSEX T380D AND T430D** are two mid-range hedge cutters designed for use within the groundcare and agricultural market sectors.

With a 3.84m and 4.33m reach respectively, the arm of the T380D and T430D is fabricated from heavy gauge circular steel tube, which offers maximum resistance to torsion stress, whilst the moulded polypropylene hydraulic oil tank is designed to significantly reduce the overall weight. A thermostatically controlled oil cooler is available as an optional extra. Both models are fitted with a 1m width cutting head, a mechanical break-away device and a choice of Y-pattern or Bootie flails.



Cable controls



Mono lever electric controls



SCAN  
TO SEE  
**T430D**  
HEDGE  
CUTTERS



## **KEY FEATURES & BENEFITS**

**DELTA BOX FRAME** – For maximum strength

**CHOICE OF CABLE OR MONO-LEVER ELECTRIC CONTROLS**

**UNIQUE ROUND, TUBULAR ARMS** – For maximum torsional strength HTR (High Torsion Resistant)

**DROP FORGED ARM LINKAGES**

**FLOATING FLAIL HEAD**

**CHOICE OF 2 FLAIL TYPES**

**DURABLE POLYPROPYLENE HYDRAULIC OIL TANK**

**FRONT & REAR HEAD PROTECTION GUARDS**

**MECHANICAL BREAKAWAY**

**FULLY INDEPENDENT HYDRAULICS**

**OPTIONAL OIL COOLER WITH THERMOSTAT**

**ADJUSTABLE ROLLER**

**REVERSIBLE ROTOR**

**MECHANIC ROLL OVER PROTECTION SYSTEM (SAB)**

**OIL AND PTO SHAFT**

**OPTIONAL LIFT FLOAT**

# WESSEX T380D/T430D HEDGE CUTTERS



The polypropylene oil tank is separated from the frame which allows it to be isolated from any structural stress. Fully recyclable.



Circular section of the arms H.T.R. (High Torsion Resistance).

## OPTIONS




Oil cooler with thermostat.



Optional lift float accumulator allows smooth operation with reduced bounce on the arm.

## T380D & T430D WORKING POSITIONS



## FLAIL BLADE OPTIONS




1 Y-pattern flails are fitted as standard.



2 Bootie flails

KEY	T380D	T430D	T380D	T430D
A	3.9m	4.4m	G	1.5m 1.65m
B	2.5m	2.96m	H	3.44m 3.95m
C	-	-	I	1.1m 1.1m
D	3.03m	3.5m	M	0.7m 0.7m
E	4.3m	4.8m	N	0.4m 0.4m
F	0.73m	0.73m		

SPECIFICATIONS	T380D	T430D
Cutting width	1m	1m
Max horizontal reach	3.9m	4.4m
Flail head angle	235°	235°
Rotor speed	3000rpm	3000rpm
Blade tip speed	60m/sec	60m/sec
Max motor power	31hp	31hp
Max power to the rotor	20hp	20hp
Oil tank capacity	70L	70L
Weight	490kg	495kg
Tractor horsepower	40-60hp	50-70hp
Min tractor weight	1700kg	2000kg
Min tractor width	1.5m	1.7m
Category linkage	1&2	1&2



The dynamically balanced rotor has the blades situated in a spiral pattern for smooth operation.



The **T500G AND TPE600** are the flagship models of the Wessex hedge cutting range. Both feature a 1.2m working width head with the option of various flail types for different applications.

The T500G has a reach of 5.0m and features a parallel arm for ease of operation, whilst the TPE600 has the advantage of a 5.96m reach. Both machines offer the option of cable controls or the EP-Tronic proportional control joystick for accurate manoeuvrability.



SCAN  
TO SEE  
**T500G & TPE600**  
HEDGE CUTTERS



Cable controls



Electric-hydraulic proportional controls with the activation of the rotor from the console



**KEY FEATURES & BENEFITS**

**T500G**

- FLOATING FLAIL HEAD**
- CHOICE OF CABLE CONTROLS OR PROPORTIONAL JOYSTICK**
- CHOICE OF FLAIL TYPES 1-3**
- PARALLEL ARM**
- DURABLE POLYPROPYLENE HYDRAULIC OIL TANK**
- 90° POWER SLEW**
- FRONT & REAR HEAD PROTECTION GUARDS**
- ADJUSTABLE ROLLER**
- FULLY INDEPENDENT HYDRAULICS**
- REVERSIBLE ROTOR (DSR)**
- MECHANICAL ROLLOVER PROTECTION (SAB)**
- HYDRAULIC BREAKAWAY**
- OPTIONAL LIFT FLOAT FOR FIRST ARM**
- OPTIONAL OIL COOLER WITH THERMOSTAT**
- OIL AND PTO SHAFT**


**TPE600E**

- FLOATING FLAIL HEAD**
- CHOICE OF CABLE CONTROLS OR PROPORTIONAL JOYSTICK**
- CHOICE OF FLAIL TYPES 1-6**
- 115° POWER SLEW**
- FRONT & REAR HEAD PROTECTION GUARDS**
- ADJUSTABLE ROLLER**
- FULLY INDEPENDENT HYDRAULICS**
- REVERSIBLE ROTOR (DSR)**
- OIL COOLER WITH THERMOSTAT**
- HYDRAULIC BREAKAWAY**
- MECHANICAL ROLLOVER PROTECTION (SAB)**
- OPTIONAL LIFT FLOAT**
- OPTIONAL BUMPER WITH LIGHTS**
- OIL AND PTO SHAFT**

# TPE600 WESSEX HEDGE CUTTERS




The TPE600 has the capability of 115° slewing action.



## SPECIFICATIONS **T500G** **TPE600**

Cutting width	1.2m	1.25m
Max horizontal reach	5m	5.96m
Flail head angle	235°	235°
Rotor speed	3100rpm	3100rpm
Blade tip speed	60m/sec	64m/sec
Max motor power	44hp	50hp
Max power to the rotor	34hp	42hp
Oil tank capacity	120L	137L
Weight	860kg	1050kg
Tractor horsepower	50-80hp	70-90hp
Min tractor weight	2800kg	3200kg
Min tractor width	1.9m	2.2m
Category linkage	2	2

## T500G & TPE600 WORKING POSITIONS



## FLAIL BLADE OPTIONS



**1** Standard 'Y' Pattern flail



**2** Spoon flail



**3** 'T' Pattern flail



**4** Articulated 'Y' Pattern flail



**5** Bootie flail



**6** Hedge trimming flail

## KEY **T500G** **TPE600**

A	4.85m	F	1.53m	A	5.96m	L	1.14m
B	5.08m	G	1.53m	B	6.18m	M	2.55m
C	3.34m	H	4.96m	C	3.31m	N	2.42m
D	3.28m			D	4.36m	O	2.95m
E	4.44m			E	5.54m	P	1.42m
				I	2.16m		



The **WESSEX MTC/MTX TRAILED COLLECTORS** are available as a sweeper collector or a paddock cleaner in both PTO or engine driven versions for use behind a small tractor or an ATV or UTV.

As a sweeper collector, the machine is fitted with supple bristles for turfcare applications. Grass clippings, autumn leaves and other debris will be flicked effortlessly into the hopper without damaging fine turf. The paddock cleaner version is fitted with a row of sprung steel tines in front of the rotor which loosens stubborn muck. The rotor is fitted with a heavy-duty bristle for maximum efficiency in a paddock environment. When full, the hopper is rolled over by means of a hand-operated winch to leave a clean discharge onto the ground.



**W SPECIFICATIONS DUNG BEETLE MTX120/MTC120**

Working width	1.2m
Overall width	1.85m
Hopper capacity	0.7m <sup>3</sup> (approx.)
Weight	317kg

**DOMESTIC AND COMMERCIAL HORSE OWNERS NEED TO KEEP PADDOCKS CLEAN, TIDY AND FREE OF DROPPINGS TO MAINTAIN A HEALTHY ENVIRONMENT FOR HORSES.**



With the **STX Paddock Cleaners** in 1.2m or 1.8m widths, the chore of collecting horse muck is turned into a pleasure.

The strong and simple sweeping action of this machine will collect horse droppings, twigs and other debris into the hopper whilst the grass benefits from the regular grooming action of the bristles – an advantage not gained from vacuum machines. A powerful hydraulic ram tips debris from the hopper at a height of 1.3m into a low trailer or heap on the ground.



**NO MUCK,  
NO WORMS  
HEALTHY  
HORSES**



**KEY FEATURES & BENEFITS**

**HARD WEARING POLYPROPYLENE BRISTLES** – Clean sweep every time.

**BRUSHES EASILY REPLACEABLE** – Ease of maintenance

**GROOM THE Paddock AS YOU SWEEP** – Generate new fresh grass

**HYDRAULIC TIP** – Clean discharge



**SPECIFICATIONS** **STX-120** **STX-180**

Working width	1.2m	1.8m
Overall width	1.6m	2.2m
Hopper capacity	1.5m <sup>3</sup>	2.25m <sup>3</sup>
Tipping height	1.3m	1.3m
Weight	530kg	645kg
Minimum power required	18hp	25hp

## Mode 1

### STC SWEEPER COLLECTOR

Collects autumn leaves and debris brilliantly.

When in sweeping mode, the STC is fitted with the brush rotor comprising 4 banks of hard-wearing polypropylene bristles which will lift autumn leaves, grass clippings and litter effortlessly into the hopper. The bristles, which are secured firmly into a pre-drilled strip with a wire staple, are a generous length to give a good 'flick' action ensuring that the material is thrown to the back of the hopper.

## Mode 2

### STC FLAIL COLLECTOR

Tackling long or short grass is no problem!

As a flail collector, the STC is fitted with a large diameter steel drum rotor with 4 rows of closely spaced flails, and 2 rows of draft paddles to create the suction for collecting the grass. The STC has no narrow throat as with many collectors, therefore long or short grass will be collected efficiently without blocking even in wet conditions.

Not only will the STC leave a fine finish on short turf, but is also ideal for end of season clearance of wild flower areas or golf course rough.

## Mode 3

### STC SCARIFIER COLLECTOR

Leaves sports turf at the top of it's game!

When in scarifying mode, the flail blades are replaced with 2mm verti-cutting knives for a professional scarifying operation. Ideal for sports field work or lawns, the STC scarifier will leave a clean cut through the turf at approx. 30mm centres and will collect the debris in one pass.



SCAN  
TO SEE  
A DEMO  
STC  
MODES AS...




**SWEeping  
LEAVES**



**FLAIL  
COLLECTING**


1



2



3



## Mode change

Whatever mode the STC is purchased in, the option change kits allows the machine to be simply converted to perform the other 2 functions.

### OPTION CHANGE KITS

FROM	TO	STC-120	STC-180
Scarifier	Flail mower (flails only)	OCK 3	OCK 10
Scarifier	Flail mower (rotor change)	OCK 6	OCK 13
Scarifier	Sweeper	OCK 5	OCK 12
Flail mower	Scarifier (flails only)	OCK 4	OCK 11
Flail mower	Scarifier (rotor change)	OCK 7	OCK 14
Flail mower	Sweeper	OCK 5	OCK 12
Sweeper	Scarifier	OCK 1	OCK 8
Sweeper	Flail mower	OCK 2	OCK 9

### SPECIFICATIONS STC-120 STC-180

Working width	1.2m	1.8m
Overall width	1.6m	2.2m
Hopper capacity	1.5m <sup>3</sup>	2.25m <sup>3</sup>
Weight (in sweeper mode)	520kg	635kg
Power required	18hp	25hp



Mode 1

 **STC SWEEPER COLLECTOR**



Mode 2

 **STC FLAIL COLLECTOR**



Mode 3

 **STC SCARIFIER COLLECTOR**



**WESSEX HYDRAULIC TIPPING TRAILERS** are available in 3 sizes; 1.25ton, 1.5 ton & 3 ton gross weights. Aimed at the private estate, hobby farmer, groundscape & golf course applications, these popular trailers are ideal for hauling a variety of materials.

The optional weld-mesh extension sides are available on all models and will increase the carrying capacity when transporting bulky materials i.e. grass clippings and leaves etc.

## WESSEX KEY FEATURES & BENEFITS

- ALL-STEEL CONSTRUCTION** – Durability
- REMOVABLE SIDES** – Versatility
- HINGED TAILGATE** – Ease of emptying
- TURF TYRES** – Minimal turf compaction
- OPTIONAL EXTENSION SIDES** – Increased carrying capacity
- OPTIONAL LIGHTING KIT** – Be seen in the dark!



WESSEX SPECIFICATIONS	T-125	1.5T-LGPW
Bed length	1.9m	2.1m
Bed width	1.1m	1.2m
Overall length	2.7m	3.14m
Side height	0.35m	0.38m
Bed height	0.6m	0.65m
Weight capacity	1.25 ton gross	1.5 ton gross
Tyre size	20x8x10	23x10.5x12
Trailer weight	273.5kg	342.5kg

	3.0T-LGPW
Bed length	2.5m
Bed width	1.5m
Overall length	3.55m
Side height	0.39m
Bed height	0.7m
Weight capacity	3.0 ton gross
Tyre size	26x12x12
Trailer weight	448.5kg



**WESSEX MOUNTED SPREADERS**

are an excellent addition to any fleet of groundcare equipment. Built to provide an economical yet extremely effective means of spreading fertiliser, seed, lime or dry salt these spreaders in 270 and 360 litre capacity simply connect to the tractor's 3 point hitch and PTO.

**KEY FEATURES & BENEFITS**

**270 & 360 LITRE CAPACITIES** – A machine for every application

**STAINLESS STEEL DISC** – Resistance against corrosion

**ADJUSTABLE FINS** – Alter spread pattern

**OPTIONAL WINTER KIT** – Ideal for winter maintenance applications (See page 15)

**WILL SPREAD A WIDE VARIETY OF MATERIALS**

**ALSO AVAILABLE WITH A NON-CORROSIVE POLYPROPYLENE HOPPER.**

**SPECIFICATIONS** *FS-270* *FS-360*

Hopper Capacity	270 litres	360 litres
Hopper Capacity kilos	350 kilos	466 kilos
Height	1.05m	1.13m
Weight	58kg	63kg
Spread width	Up to 14m	Up to 14m

# WESSEX FS170T/FS270T SPREADERS



SCAN  
TO SEE  
A DEMO  
ATV  
SPREADER



Spread limiter



Extended agitator

The Wessex **TRAILED SPREADERS** are ideal for use behind ATV's and UTV's.

Available with 170 litre or 270 litre hoppers, these popular spreaders will spread granular or powdered fertilisers or grass seed in a turf care application, game feed on estate or even dry granular salt for winter maintenance.

The salt spreader versions include the following additional features:

**SPREAD LIMITER** – Typically used in winter maintenance applications for spreading salt on pathways, the spread limiter restricts the application width to approximately 1.5m.

**EXTENDED AGITATOR** – Keeps material moving within the hopper.

**FILTERING GRID** – Breaks up lumps of salt before entering the hopper.



Optional plastic hopper



Filtering grid

## WESSEX SPECIFICATIONS FS-170T FS-270T

<b>Hopper Capacity (granular, fertiliser)</b>	170 litres	270 litres
<b>Height</b>	218 kilos	345 kilos
<b>Weight</b>	1.3m	1.43m
<b>Spread width</b>	80kg	84kg
	Up to 14m	Up to 14m

*Sweep up to 450 miles before changing the bristles!*

The unique modular brush system that is extremely efficient and economical for all commercial sweeping!

- ✓ **TACKLES BULKY MATERIALS**
- ✓ **WILL 'SQUEEGEE' WET SURFACES**
- ✓ **GENERATES MINIMAL DUST**
- ✓ **IS HIGHLY DURABLE**
- ✓ **SUPERB QUALITY**
- ✓ **IS THE EFFICIENT SWEEPING SOLUTION**
- ✓ **THE ORIGINAL AND THE BEST!**

Why BroomEx?

- DO YOU WANT TO KEEP THE PREMISES TIDY?**
- CONCERNED ABOUT HEALTH & SAFETY?**
- DO YOU HAVE LIMITED FREE TIME?**

From building sites to farmyards the versatile BroomEx sweeper system saves time and money. With no moving parts to increase the danger of flying debris, BroomEx is safe and maintenance-free.

Attach a BroomEx brush quickly and simply to your host vehicle and off your go! A wide range of hitches enables BroomEx to be attached to compact and large tractors, telehandlers, forklifts, loaders and skidsteers.

**W** **KEY FEATURES & BENEFITS**

**SWEEP UP TO 450 MILES BEFORE CHANGING THE BRISTLES** – Save time and money

**A WIDE RANGE AVAILABLE** – A push broom to suit any sweeping application

**UNIQUE PATENTED FEATURES** – A superior sweeping performance

**A WIDE RANGE OF HITCHES** – Mount the BroomEx to the machine of your choice

**NO MAINTENANCE REQUIRED** – Zero downtime

**4MM HOOD THAT HAS BEEN SHOTBLASTED, UNDERCOATED AND POWDERCOATED** – Extremely robust

**HARD WEARING POLY BRISTLES** – Longevity

**NO STORAGE STAND REQUIRED** – Simple storage for when not in use

**OPTIONAL MAGNETIC BARS** – No more punctures or injured livestock

**CHANGE THE BRISTLES WITH EASE**



**W** **THE RANGE**




**W** **C-MAX SERIES**

**11 ROWS OF BRISTLES**  
Working widths: 2.4m, 1.8 and 1.5m



**W** **BM SERIES**

**11 ROWS OF BRISTLES**  
Working widths: 2.4m, 1.8 and 1.5m



**W** **BP SERIES**

**8 ROWS OF BRISTLES**  
Working widths: 2.4m, 1.8m, 1.5m

**W** **PLUS...**



- NO MOVING PARTS**
- NO BELTS OR CHAINS**
- NO MOTOR**
- NO DOWNTIME**
- NO PROBLEM**

## AVAILABLE HITCHES



C-Max fork sleeve hitch



C-Max fork sleeve hitch for 150mm forks



C-Max 3 point linkage hitch



C-Max telehandler quick hitch



C-Max Skid steer hitch



C-Max Bucket guide hitch



The innovative **BROOMEX 'C-MAX'** combines the well-known **BROOMEX** concept of a heavy duty push broom together with the patented side retainers, which will hold bulk volumes of material in front of the brush without spillage.

The end brushes are carefully twisted to pull material away from a curb or wall and into the main path of the broom. This ensures a clean sweep right into those awkward corners without the danger of the hood damaging the wall. Sweeping times will be reduced even further, as those frustrating spill lines will be eliminated with the new BroomEx 'C-Max'.

## **KEY FEATURES & BENEFITS**

**PATENTED TWISTED END BRUSHES** – Sweep close to a wall and push debris in path of broom

**ELIMINATES END SPILLAGE** – 65% faster than a standard push broom

**WILL MOVE BULK VOLUMES OF MATERIAL** – Minimise your sweeping time

**AVAILABLE IN 1.5M, 1.8M AND 2.4M WIDTHS** – Versatile

**FITTED WITH EDGE MARKER KIT AS STANDARD** – Broom edge clearly visible from the cab

### **SPECIFICATIONS**

	<b>BM-150 C-MAX</b>	<b>BM-180 C-MAX</b>	<b>BM-240 C-MAX</b>
<b>Width</b>	1.5m	1.8m	2.4m
<b>Brush rows</b>	11	11	11
<b>Weight</b>	117.5kg	132.5kg	166.5kg
<b>Bristle height</b>	280mm	280mm	280mm

*The push broom with a twist - Up to 65% faster than a standard push broom*



**BROOMEX  
C-MAX OFFERS...**

- ✓ **NO SIDE SPILL**
- ✓ **A CLEAN SWEEP**
- ✓ **HOLD BULK VOLUMES OF MATERIAL**
- ✓ **65% FASTER THAN A CONVENTIONAL PUSH BROOM**
- ✓ **SWEEP CLOSE TO A WALL**



SCAN  
TO SEE  
A DEMO  
**BROOMEX  
C-MAX**



**SWEEP AGAINST A WALL**



**HOLD BULK VOLUMES**



## AVAILABLE HITCHES



BM fork sleeve hitch



BM fork sleeve hitch for 150mm forks



BM 3 point linkage hitch



BM telehandler quick hitch



BM Skid steer hitch



BM Bucket guide hitch



**BROOMEX BM PUSH BROOMS** have 11 rows of bristles for maximum sweeping power in demanding applications. Ideal for use with full sized tractors and telehandlers.

Hitch options include fork sleeve hitch, three-point tractor hitch or custom hitches to suit any type of materials handler, loader or skidsteer. Available in 1.5m, 1.8m widths and 2.4m widths.

*Save up to 98%  
on labour time!*



SCAN  
TO SEE  
A DEMO  
**BM PUSH  
BROOMS**



### SPECIFICATIONS

	<b>BM-150</b>	<b>BM-180</b>	<b>BM-240</b>
<b>Width</b>	1.5m	1.8m	2.4m
<b>Brush rows</b>	11	11	11
<b>Weight</b>	94kg	109kg	143kg
<b>Bristle height</b>	280mm	280mm	280mm



BP 3 point linkage hitch



BP bucket hitch



BP skidsteer hitch



*5 men sweeping for 1 hour or  
1 man sweeping for 5 minutes!*

\* COMPARISON BETWEEN USING MANUAL YARD BROOMS Vs A BROOMEX

**BROOMEX BP** with 8 rows of bristles, is ideal for counter-balance fork trucks and compact tractors.

An integral fork hitch is standard, however three-point or skidsteer hitches may be specified as options. Available in 1.5m and 1.8m widths.



**SCAN  
TO SEE  
A DEMO  
BP PUSH  
BROOMS**



### SPECIFICATIONS

	<b>BP-150</b>	<b>BP-180</b>	<b>BP-240</b>
<b>Width</b>	1.5m	1.8m	2.4m
<b>Brush rows</b>	8	8	8
<b>Weight</b>	67kg	79kg	116kg
<b>Bristle height</b>	280mm	280mm	280mm

# APPLICATIONS

FOR BROOMEX PUSH BROOMS



 SNOW **CLEARANCE**



 BUILDERS **MERCHANTS**



 GARDEN **CENTRES**



 GOLF **COURSES**



 LIVERY **YARDS**



 LIVESTOCK **YARDS**



 SAW **MILLS**



 VEHICLE **BREAKERS**

# APPLICATIONS

FOR BROOMEX PUSH BROOMS



 **CONCRETE PLANTS**



 **CONSTRUCTION SITES**



 **GRAIN STORES**



 **LANDSCAPE MAINTENANCE**



 **COMPOSTING FACILITIES**



 **RECYCLING CENTRES**



 **WAREHOUSE & DISTRIBUTION SITES**

*When only the best will do...*



**SCAN HERE  
TO SEE THE  
RANGE**





The **WESSEX LS100 LOGSPLITTER** turns a chore into an enjoyable task! With up to 10 ton of splitting force\* at its disposal, the LS100 will effortlessly crack logs up to 18"/450mm in height.

A floor-level platform means loading logs onto the splitter is safe and easy, whilst two-handed operation keeps the operator protected.

The **WESSEX HLS-100 HORIZONTAL LOG SPLITTER** makes log splitting a breeze. Building on the success of the vertical Wessex LS-100 splitter, the HLS-100 allows you to load logs directly from a trailer bed to the splitter at the same level, therefore avoiding painful backache.

Simply place a log on the platform, push the handles and watch as the 10ton splitting force effortlessly parts the wood.

The HLS-100 is built tough and is manufactured with a log chute as standard, which conveys the split logs into a trailer or barrow ready to be transferred to a storage shed.

## WESSEX SPECIFICATIONS LS-100 HLS-100

Weight	65kg	126.5kg
Height	1450mm	1140mm
Width	850mm	1480mm
Depth	590mm	670mm
Linkage	Cat 1	
Pipe fittings (LS-100 & HLS-100)	½ inch quick release probes	
Minimum power required	30hp+	30hp+

## WESSEX KEY FEATURES & BENEFITS

**POWERFUL 10 TON SPLITTING FORCE** – Crack the toughest logs!

**2 HAND CONTROL** – Meets HSE requirements

**SIMPLISTIC DESIGN** – Easy to use

\* depending on tractor's hydraulic system



SCAN TO SEE A DEMO LS-100 LOG SPLITTER





 **AFTER-SALES & SERVICE**



 **DEALER NETWORK**



 **SPARE PARTS**

## **WESSEX AFTER-SALES & SERVICE BACK-UP**

At Wessex International, our care for the customer does not stop at the time of machine purchase. Our dedicated after-sales team with their wealth of experience are here to tend to your needs throughout the working life of the machine. Whether it's machine operation, advice on application, or a technical question over maintenance, we're here to help.

## **DEALER NETWORK**

Wessex products are sold exclusively through the Wessex UK dealer and global distributor network. Our dealers have the market knowledge and experience to recommend the correct product for your application, and their in-house service and maintenance department provides a local centre for all your after service requirements.

## **SPARE PARTS**

Only genuine Wessex spare parts should be used to maintain optimum performance from your Wessex machine. To minimise costly machine downtime, parts orders are dispatched daily to our professional dealer network by next-day carrier service (UK mainland), and 2 day for UK Highlands & Islands. If ordered before 1:00pm, parts will be dispatched the same day (subject to availability).

**T:** 01264 345878 **E:** [parts@wessexintl.com](mailto:parts@wessexintl.com)



**MANUFACTURING EXCELLENCE SINCE 1962**

Dealer stamp



**WESSEX INTERNATIONAL** Charlton House, Caxton Close, East Portway Ind. Est., Andover, Hampshire, SP10 3QN  
**T:** 01264 345870 **F:** 01264 345880 **E:** sales@wessexintl.com [www.wessexintl.com](http://www.wessexintl.com) Follow us on:  

L478. © Wessex International 2017. E&OE. Specifications may change without notice. Wessex International is a trading name of Wessex International Machinery.

