## 2026 OUTLANDER ELECTRIC T



## PACKAGE HIGHLIGHTS

- · Liquid-cooled system : Battery, inverter, motor and on-board charger
- · Charging from 20% to 80% in as low as 50 min
- · Up to 47 miles (75 km) of range
- · High and Low gear allowing full work capacity
- $\cdot$  Engine modes and speed limiter
- · Dedicated tires for optimal noise and vibrations level
- · 3-level regen braking
- · On-the-fly reverse capabilities
- · 5 in. colored display
- · Front and rear bumpers
- · LED headlights and tail lights, specific LED POD light
- · Tow ball, mirrors, flashers

ENGINE	Electric
Туре	47 hp / 53 lb-ft, ROTAX® E-POWER, Liquid-cooled
Power	Peak: 47 hp (35 kW) Continuous: 27 hp (20 kW)
Torque motor	Peak: 53 lb-ft (72 Nm) Continuous: 21 lb-ft (28Nm)
Top Speed/Sustained	High gear: 37 mph (60 km/h) Low gear: 28 mph (45 km/h)
BATTERY	
Battery type	Integrated, Lithium-ion
Battery operating temperature range	From -20°C to 40°C (-4 Fahrenheit to 104 Fahrenheit)
Battery capacity	8.9 kWh
Cooling system	Liquid-cooled : Battery, inverter and on-board charger Integrated AC heater for charging at low temperature
Estimated range (when fully charged)	Tested in accordance with WMTC*: 50 miles (80 km) Average utility range*: 31 miles (50 km)
Fonction	Regen braking with 3 levels adjusments
Charger	On-board charger 6.6 kW Level 2 (compatible with level 1 charging)
Connector type	Type 2 IEC 62196 with integrated LED light
Charging time Level 2 (240 V)	50 min (20 - 80 %) 1 hour 30 min (0 - 100%)
Charging time Level 1 (120 V)	3 hours 10 min (20 - 80%) 5 hours 15 min (0 - 100%)
DRIVE TRAIN	
Transmission	L/N/H/P Reverse activated via start button
Drive Train	Selectable 2WD / 4WD with Visco-Lok† QE auto-locking front differential
Driving assistance	Work / Standard / Sport modes Speed limiter
Power Steering	Tri-Mode Dynamic Power Steering (DPS)
SUSPENSIONS	
Front Suspension	Double A-arm 9.75 in. (24.8 cm) travel
Front Shocks	Twin tube
Rear Suspension	Double A-arm 10.25 in. (26 cm) travel
Rear Shocks	Twin tube

Front & Rear Tires	XPS Recon Force 26 x 8/10 x 14 in.
Wheels	14 in. cast aluminum
BRAKES	
Front	Dual 214 mm disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm disc brake with hydraulic twin-piston caliper
DIMENSIONS / CAPAC	ITIES
Estimated Dry Weight	885 lb (402 kg)
LxWxH	89.9 x 48.1 x 49.6 in. (228.3 x 122.2 x 126 cm)
Wheelbase	53 in. (134.5 cm)
Ground Clearance	12 in. (30.5 cm)
Seat Height	38 in. (96.7 cm)
Rack Capacity	Front: 120 lb (54.4 kg) / Rear: 240 lb (109 kg)
Storage Capacity	9 gal (34 L)
Towing Capacity	1,830 lb (830 kg)
FEATURES	
Gauge	5 in. colored display
DC - DC converter	Continuous 500W (at all speed including at idle)
Instrumentation	Phone charger with 1xUSB-A and 1xUSB-C outputs
Ingnition	RF Digitally Encoded Security System (D.E.S.S.™)
Lighting	LED headlights and tail lights LED signature LED POD light
Winch	N/A
Seat	Standard
Handlebar	Standard
Protection	Front and rear bumpers Full skid plate
Hitch Type	2 in, hitch receiver with towball





Battery: 5 years (12,427 miles / 20,000 km limit)

Vehicle: 2-year BRP Limited warranty

**WARRANTY & EXTENDED SERVICE** 

Factory warranty

