2026 MAVERICK R X RS 999T DCT/SAS



PACKAGE HIGHLIGHTS

- 77 in. 4 Link Trailing arm with aluminum HD tall knuckle
- Smart-Lok^{™*} front differential
- FOX† 3.0 PODIUM RC2† Piggyback with bypass, dual speed compression and rebound adjustments
- · 10.25 in. touchscreen display
- 32 in. ITP XNR Tenacity tires
- 16 in. flow formed beadlock wheels
- Front and rear camera
- Telescopic steering wheel with infotainment controls
- Full hard roof
- Full plastic skid plate
- · 4-point harness with shoulder pads
- · Premium high-performance LED headlights
- Can-Am LED signature
- Center dashboard storage with cell phone holder
- · X-package graphics/seats
- 1700-W Magneto
- · Horn with carling
- RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button

R X rs 999T DCT SAS

· Smart-Shox Technology featuring Live Valve Gen 3

DIRACHIOLONIO / GADAGITICO

ENGINES	999T DCT	999T DCT - SAS
Туре	240 hp, Rotax 999T engine, 999 cc Turbocharged Triple-cylinder engine, liquid cooled with integrated intercooler and highperformance air filter	240 hp, Rotax 999T DCT engine, 999cc Turbocharged Triple- cylinder engine, liquid cooled with integrated intercooler and high- performance air filter
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)	
Transmission	Rotax DCT, 7 Speed with High & Low range	
Drive Train	Lockable front differential with exclusive Smart-Lok* True 2WD / 4WD with front diff. lock / 4WD TRAIL ACTIV / 4WD TRAIL	
Power Steering	Gen 2 Tri-mode DPS High torque	
SUSPENSIONS		
Front Suspension	Forged Aluminum heavy duty Tall Knuckle - Double A-arm with sway bar / 25 in. (63.5 cm) suspension travel	
Front Shocks	FOX† 2.5 PODIUM RC2† Piggyback with bypass, dual speed compression and rebound adjustments	FOX† 2.5 PODIUM† Piggyback with bypass and Smart-Shox technology featuring Liw Valve Gen 3 (Dual Valve compression & rebound
Rear Suspension	4 Link Trailing arm with Forged Aluminum heavy duty Tall Knuckle / 25.5 in. (64.8 cm) suspension travel	
Rear Shocks	FOX† 3.0 PODIUM RC2† Piggyback with bypass, dual speed compression and rebound adjustments	FOX† 3.0 PODIUM† Piggyback with bypass and Smart-Shox technology featuring Live Valve Gen 3 (Dual Valve compression & rebound
TIRES / WHEELS		
Front / Rear Tires	ITP XNR Tenacity 32 x 10 x 16 in.	
Wheels	16 in. Aluminum FlowFormed Beadlock	
BRAKES		
Front	32 mm hydraulic triple piston caliper with a 265 mm disc	
Rear	30 mm hydraulic twin piston caliper with a 255 mm disc	

Cage	High strengh (Dual phase) steel tubing and stampings	
Estimated Dry Weight*	2,240 lb (1,016kg)	
LxWxH	140 x 78.1 x 71.5 in. (355.6 x 198.5 x 181.5 cm)	
Wheelbase	108 in. (274.3 cm)	
Ground Clearance	17 in. (43.2 cm)	
Cargo Box Capacity	200 lb (90 kg)	
Storage Capacity	Total: 2.1 gal (8.1 L)	
Fuel Capacity	13.2 Gal (50 L)	
FEATURES		
Gauge	4.5 in. wide digital display with keypad & 10.25 in. touchscreen display	
Magneto	1700-W	
Instrumentation	USB A (2 charging port & 1 communication port) DC outlet (10-A)	
Lighting	Premium high-performance LED headlights Can-Am LED signature	
Winch	Winch-ready bumper (4,500 lb / 2,041 kg winch no installed)	
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button	
Protection	Full hard roof Premium half doors Front lower deflector Front / Rear anchor Full plastic skid plate	
WARRANTY & EXTENDED S	ERVICE	
Factory warranty	2-year BRP limited warranty	
	· · · · · · · · · · · · · · · · · · ·	



Triple Black



