

**COMPACT LOADERS
WHEEL LOADERS
TELESCOPIC WHEEL LOADERS**



PRODUCT RANGE 2017/II



Schaeffer

Tipping loads and parallel motion are not guarantee when using a foreign headstock.

Tipping load were measured with standard machines and pallet forks.

Compact Wheel Loaders	2020	4
	2024	5
	2024 SLT	6
	2028	7
	2028 SLT	8
	2030 SLT	9
	2032	10
	2034	11
	2336	12
	2336 SLT	13
	2345	14
	2345 SLT	15
	3545	16
	3550	17
	3550 SLT	18
	4250	19
Wheel Loaders	4350 Z	20
	5650 Z	21
	5680 Z	22
	6680 Z	23
	8600 Z	24
Telescopic Wheel Loaders	2345 T	25
	2345 T SLT	26
	3550 T	27
	3550 T SLT	28
	5650 T	29
	5680 T	30
	6680 T	31
	8610 T	32
	9640 T	33
	9660 T	34
Attachments		35-45
Importers		46-48
Notes		49-51

Technical Specifications:

Engine:	3-cyl.-watercooled Kubota diesel engine 15 kW = 20 hp
Tyres:	7.00-12 AS
Width:	790 mm-1.000 mm
Height with protection roof:	2.070 mm
Lifting height:	2.470 mm
Length incl. bucket:	3.330 mm
Turning radius:	530 mm
Operating weight:	1.400 kg
Lifting capacity:	1.200 kg
Tipping load, straight (pallet fork)*:	605 kg-749 kg
Tipping load, straight (bucket)*:	728 kg-871 kg
Speed:	0-12 km/h
* acc. to ISO 8313 (Boom horizontal)	

**As standard:**

Hydraulic four wheel drive with foot pedal control, Genuine Schäffer axle, Restraining system for protective roof, Drum brake as service and hand brake, Maintenance free articulated pendulum joint, 1 x LED headlamp front, Parallel lift and quick hitch, Third hydraulic function with control handle, Working hydraulics: 31 l/min, Hour meter, fuel control lamp and temperature gauge.

Technical Specifications:

Engine:	3-cyl.-watercooled Kubota diesel engine 19 kW = 26 hp
Tyres:	7.00-12 AS
Width:	890 mm-1.240 mm
Height with protection roof:	from 2.090 mm
Lifting height:	2.800 mm/3.060 mm**
Length incl. bucket:	3.530 mm
Turning radius:	660 mm
Operating weight:	1.700 kg
Lifting capacity:	1.400 kg
Tipping load, straight (pallet fork)*:	622 kg-786 kg
Tipping load, straight (bucket)*:	829 kg-973 kg
Speed:	0-12 km/h
* acc. to ISO 8313 (Boom horizontal)	
** high lift version	



As standard:

Hydraulic four wheel drive with foot pedal control, Genuine Schäffer axle, Drum brake as service and hand brake, Maintenance free articulated pendulum joint, Restraining system for protective roof, 1 x LED headlamp front, Parallel lift, Third hydraulic function with control handle, Working hydraulics: 33 l/min, Hour meter, fuel control lamp and temperature gauge, Headstock SWH with hydraulic tool lock.

Technical Specifications:

Engine:	3-cyl.-watercooled Kubota diesel engine 19 kW = 26 hp
Tyres:	7.00-12 AS
Width:	890 mm-1.240 mm
Height with protection roof:	from 1.890 mm
Height with cab:	from 1.890 mm
Lifting height:	2.800 mm
Length incl. bucket:	3.630 mm
Turning radius:	760 mm
Operating weight:	1.750 kg
Lifting capacity:	1.400 kg
Tipping load, straight (pallet fork)*:	787 kg-939 kg
Tipping load, straight (bucket)*:	1.037 kg-1.187 kg
Speed:	0-12 km/h
* acc. to ISO 8313 (Boom horizontal)	



As standard:

Low style loader, Combined oil cooler, Hydraulic four wheel drive with foot pedal control, Genuine Schäffer axle, Restraining system for protective roof, Drum brake as service and hand brake, Maintenance free articulated pendulum joint, 1 x LED headlamp front, Parallel lift, Adjustable steering column, Third hydraulic function with control handle, Working hydraulics: 33 l/min, Hour meter, fuel control lamp and temperature gauge, Counter weight rear end, Headstock SWH with hydraulic tool lock.

Technical Specifications:

Engine:	3-cyl.-watercooled Kubota diesel engine 19 kW = 26 hp
Tyres:	7.00-12 AS
Width:	890 mm-1.240 mm
Height with protection roof:	from 2.090 mm
Lifting height:	2.800 mm/3.060 mm**
Length incl. bucket:	3.530 mm
Turning radius:	660 mm
Operating weight:	1.760 kg
Lifting capacity:	1.500 kg
Tipping load, straight (pallet fork)*:	675 kg-841 kg
Tipping load, straight (bucket)*:	832 kg-976 kg
Speed:	0-15 km/h
* acc. to ISO 8313 (Boom horizontal)	
** high lift version	



As standard:

Combined oil cooler, Hydrostatic four wheel drive, Genuine Schäffer axle, Restraining system for protective roof, Drum brake as service and hand brake, Maintenance free articulated pendulum joint, 1 x LED headlamp front, Parallel lift, Third hydraulic function with control handle, Working hydraulics: 33 l/min, optional 42 l/min., Adjustable steering column, Hour meter, fuel control lamp and temperature gauge, Counter weight rear end, Headstock SWH with hydraulic tool lock.

Technical Specifications:

Engine:	3-cyl.-watercooled Kubota diesel engine 19 kW = 26 hp
Tyres:	7.00-12 AS
Width:	890 mm-1.240 mm
Height with protection roof:	from 1.890 mm
Height with cab:	from 1.890 mm
Lifting height:	2.800 mm
Length incl. bucket:	3.630 mm
Turning radius:	760 mm
Operating weight:	1.800 kg
Lifting capacity:	1.500 kg
Tipping load, straight (pallet fork)*:	787 kg-939 kg
Tipping load, straight (bucket)*:	1.037 kg-1.187 kg
Speed:	0-15 km/h
* acc. to ISO 8313 (Boom horizontal)	



As standard:

Low style loader, Combined oil cooler, Hydrostatic four wheel drive, Genuine Schäffer axle, Restraining system for protective roof, Drum brake as service and hand brake, Maintenance free articulated pendulum joint, 1 x LED headlamp front, Parallel lift, Third hydraulic function with control handle, Working hydraulics: 33 l/min, optional 42 l/min., Adjustable steering column, Hour meter, fuel control lamp and temperature gauge, Counter weight rear end, Headstock SWH with hydraulic tool lock.

Technical Specifications:

Engine:	3-cyl.-watercooled Kubota diesel engine 22 kW = 30 hp
Tyres:	7.00-12 AS
Width:	890 mm-1.240 mm
Height with protection roof:	from 1.890 mm
Height with cab:	from 1.890 mm
Lifting height:	2.800 mm
Length incl. bucket:	3.630 mm
Turning radius:	760 mm
Operating weight:	1.850 kg
Lifting capacity:	1.500 kg
Tipping load, straight (pallet fork)*:	789 kg-941 kg
Tipping load, straight (bucket)*:	1.041 kg-1.191 kg
Speed:	0-15 km/h

* acc. to ISO 8313 (Boom horizontal)



As standard:

Low style loader, Combined oil cooler, Hydrostatic four wheel drive, Genuine Schäffer axle, Restraining system for protective roof, Drum brake as service and hand brake, Maintenance free articulated pendulum joint, 1 x LED headlamp front, Parallel lift, Third hydraulic function with control handle, Working hydraulics: 33 l/min, optional 42 l/min., Adjustable steering column, Hour meter, fuel control lamp and temperature gauge, Counter weight rear end, Headstock SWH with hydraulic tool lock.

Technical Specifications:

Engine:	3-cyl.-watercooled Kubota diesel engine 22 kW = 30 hp
Tyres:	10.0/75-15.3 AS
Width:	1.050 mm-1.260 mm
Height with protection roof:	2.200 mm
Lifting height:	2.880 mm/3.110 mm**
Length incl. bucket:	3.550 mm
Turning radius:	740 mm
Operating weight:	1.850 kg
Lifting capacity:	1.600 kg
Tipping load, straight (pallet fork)*:	789 kg-941 kg
Tipping load, straight (bucket)*:	1.041 kg-1.191 kg
Speed:	0-20 km/h

* acc. to ISO 8313 (Boom horizontal)

** high lift version

**As standard:**

Combined oil cooler, Hydrostatic four wheel drive with automotive control, high-pressure drive, Genuine Schäffer axle, Multiple disk brake, maintenance free, Maintenance free articulated pendulum joint, Restraining system for protective roof, Adjustable steering column, Hour meter, fuel control lamp and temperature gauge, 1 x LED headlamp front, Parallel lift, Third hydraulic function with control handle, Working hydraulics 33 l/min., optional 42 l/min., Counter weight rear end, Headstock SWH with hydraulic tool lock.

Technical Specifications:

Engine:	3-cyl.-watercooled Kubota diesel engine 24 kW = 33 hp
Tyres:	10.0/75-15.3 AS
Width:	1.020 mm-1.290 mm
Height with protection roof:	2.180 mm
Height with cab:	2.150 mm
Lifting height:	2.880 mm/3.110 mm**
Length incl. bucket:	3.665 mm
Turning radius:	1.020 mm
Operating weight:	2.100 kg/cab 2.300 kg
Lifting capacity:	1.600 kg
Tipping load, straight (pallet fork)*:	895 kg-1.124 kg
Tipping load, straight (bucket)*:	1.110 kg-1.381 kg
Speed:	0-15 km/h
Option:	0-20 km/h

* acc. to ISO 8313 (Boom horizontal)

** high lift version



As standard:

Combined oil cooler, Hydrostatic four wheel drive, Genuine Schäffer axle, Multiple disk brake, maintenance free, Maintenance free articulated pendulum joint, Retraining system for protective roof, Adjustable steering column, Hour meter, fuel control lamp and temperature gauge, Headlamp on protective roof version: 1 x LED on the boom; cabin version: 2 x front, 1 x rear, Parallel lift, Third hydraulic function with control handle, Working hydraulics: 40 l/min, optional 48 l/min., Counter weight rear end, Headstock SWH with hydraulic tool lock.

Technical Specifications:

Engine:	4-cyl.-watercooled Kubota diesel engine 26 kW = 36 hp
Tyres:	10.0/75-15.3 AS
Width:	1.020 mm-1.570 mm
Height with protection roof:	2.215 mm
Height with cab:	2.110 mm
Lifting height:	2.880 mm/3.110 mm**
Length incl. bucket:	3.880 mm
Turning radius:	1.125 mm
Operating weight:	2.300 kg/cab 2.500 kg
Lifting capacity:	1.700 kg
Tipping load, straight (pallet fork)*:	1.048 kg-1.321 kg
Tipping load, straight (bucket)*:	1.250 kg-1.578 kg
Speed:	0-20 km/h

* acc. to ISO 8313 (Boom horizontal)

** high lift version

**As standard:**

Combined oil cooler, Hydrostatic four wheel drive, Genuine Schäffer axle, Multiple disk brake, maintenance free, Maintenance free articulated pendulum joint, Hydraulic quick gear 20 km/h switchable under load, Restraining system for protective roof, Adjustable steering column, Hour meter, fuel control lamp and temperature gauge, Headlamp on protective roof version: 1 x LED on the boom; cabin version: 2 x front, 1 x rear, Parallel lift, Third hydraulic function with control handle, Working hydraulics: 42 l/min, optional 51 l/min., Counter weight rear end, Headstock SWH with hydraulic tool lock.

Technical Specifications:

Engine:	4-cyl.-watercooled Kubota diesel engine 26 kW = 36 hp
Tyres:	10.0/75-15.3 AS
Width:	1.020 mm-1.570 mm
Height with protection roof:	from 1.950 mm**
Height with cab:	from 1.950 mm**
Lifting height:	2.880 mm
Length incl. bucket:	4.025 mm
Turning radius:	870 mm
Operating weight:	2.350 kg/cab 2.425 kg
Lifting capacity:	1.700 kg
Tipping load, straight (pallet fork)*:	1.048 kg-1.321 kg
Tipping load, straight (bucket)*:	1.395 kg-1.717 kg
Speed:	0-15 km/h
Option:	0-20 km/h

* acc. to ISO 8313 (Boom horizontal)

**with tyres 27x10.5-15 SKD



As standard:

Low style loader, Combined oil cooler, Hydrostatic four wheel drive, Genuine Schäffer axle, Multiple disk brake, maintenance free, Maintenance free articulated pendulum joint, Restraining system for protective roof, Adjustable steering column, Hour meter, fuel control lamp and temperature gauge, 1 x LED headlamp front, Parallel lift, Third hydraulic function with control handle, Working hydraulics: 42 l/min, optional 51 l/min., Counter weight rear end, Headstock SWH with hydraulic tool lock.

Technical Specifications:

Engine:	4-cyl.-watercooled Kubota turbo diesel engine 33 kW = 45 hp
Tyres:	10.0/75-15.3 AS
Width:	1.020 mm-1.570 mm
Height with protection roof:	2.215 mm
Height with cab:	2.110 mm
Lifting height:	2.880 mm/3.110 mm**
Length incl. bucket:	3.880 mm
Turning radius:	1.125 mm
Operating weight:	2.350 kg/cab 2.550 kg
Lifting capacity:	1.700 kg
Tipping load, straight (pallet fork)*:	1.048 kg-1.321 kg
Tipping load, straight (bucket)*:	1.250 kg-1.578 kg
Speed:	0-20 km/h
Option:	0-28 km/h

* acc. to ISO 8313 (Boom horizontal)

** high lift version

**As standard:**

Combined oil cooler, Hydrostatic four wheel drive, Genuine Schäffer axle, Multiple disk brake, maintenance free, Maintenance free articulated pendulum joint, Hydraulic quick gear 20 km/h switchable under load, Restraining system for protective roof, Adjustable steering column, Hour meter, fuel control lamp and temperature gauge, Headlamp on protective roof version: 1 x LED on the boom; cabin version: 2 x front, 1 x rear, Parallel lift, Third hydraulic function with control handle, Working hydraulics: 42 l/min, optional 51 l/min., Counter weight rear end, Headstock SWH with hydraulic tool lock.

Technical Specifications:

Engine:	4-cyl.-watercooled Kubota turbo-diesel engine 33 kW = 45 hp
Tyres:	10.0/75-15.3 AS
Width:	1.020 mm-1.570 mm
Height with protection roof:	from 1.950 mm**
Height with cab:	from 1.950 mm
Lifting height:	2.880 mm
Length incl. bucket:	4.025 mm
Turning radius:	870 mm
Operating weight:	2.380 kg/cab 2.455 kg
Lifting capacity:	1.700 kg
Tipping load, straight (pallet fork)*:	1.048 kg-1.321 kg
Tipping load, straight (bucket)*:	1.395 kg-1.717 kg
Speed:	0-15 km/h
Option:	0-20 km/h

* acc. to ISO 8313 (Boom horizontal)

**with tyres 27x10.5-15 SKD



As standard:

Low style loader, Combined oil cooler, Hydrostatic four wheel drive, Genuine Schäffer axle, Multiple disk brake, maintenance free, Maintenance free articulated pendulum joint, Restraining system for protective roof, Adjustable steering column, Hour meter, fuel control lamp and temperature gauge, 1 x LED headlamp front, Parallel lift, Third hydraulic function with control handle, Working hydraulics: 42 l/min, optional 51 l/min., Counter weight rear end, Headstock SWH with hydraulic tool lock.

Technical Specifications:

Engine:	4-cyl.-watercooled Kubota turbo-diesel engine 33 kW = 45 hp
Tyres:	10.0/75-15.3 AS
Width:	1.020 mm-1.390 mm
Height with protection roof:	2.270 mm
Height with cab:	2.230 mm
Lifting height:	2.950 mm/3.200 mm**
Length incl. bucket:	4.185 mm
Turning radius:	1.100 mm
Operating weight:	2.650 kg/cab 2.850 kg
Lifting capacity:	2.000 kg
Tipping load, straight (pallet fork)*:	1.523 kg-1.648 kg
Tipping load, straight (bucket)*:	1.911 kg-2.078 kg
Speed:	0-20 km/h
* acc. to ISO 8313 (Boom horizontal)	
** high lift version	



As standard:

Combined oil cooler, Hydrostatic four wheel drive, HTF (High Traction Force), Genuine Schäffer axle, Multiple disk brake, maintenance free, Maintenance free articulated pendulum joint, Hydraulic quick gear 20 km/h switchable under load, Restraining system for protective roof, Adjustable steering column, Hour meter, rev counter, fuel control lamp and temperature gauge, Headlamp on protective roof version: 1 x LED on the boom; cabin version: 2 x front, 1 x rear, Parallel lift, Third hydraulic function with control handle, Working hydraulics: 42 l/min, Counter weight rear end, Headstock SWH with hydraulic tool lock.

Technical Specifications:

Engine:	4-cyl.-watercooled Kubota diesel engine 37 kW = 50 hp
Tyres:	11.5/80-15.3 AS
Width:	1.020 mm-1.680 mm
Height with protection roof:	2.270 mm
Height with cab:	2.230 mm
Lifting height:	2.950 mm
Length incl. bucket:	4.185 mm
Turning radius:	1.100 mm
Operating weight:	2.800 kg/cab 3.000 kg
Lifting capacity:	2.000 kg
Tipping load, straight (pallet fork)*:	1.621 kg-1.739 kg
Tipping load, straight (bucket)*:	2.002 kg-2.191 kg
Speed:	0-20 km/h
Option:	0-28 km/h

* acc. to ISO 8313 (Boom horizontal)



As standard:

Combined oil cooler, Hydrostatic four wheel drive , HTF (High Traction Force), Genuine Schäffer axle, Multiple disk brake, maintenance free, Maintenance free articulated pendulum joint, Hydraulic quick gear 20 km/h switchable under load, Restraining system for protective roof, Adjustable steering column, Hour meter, rev counter, fuel and temperature gauge, Headlamp on protective roof version: 1 x LED on the boom; cabin version: 2 x front, 1 x rear, Parallel lift, Third hydraulic function with control handle, Working hydraulics: 46 l/min, optional 52 l/min., Counter weight rear end, Headstock SWH with hydraulic tool lock.

Technical Specifications:

Engine:	4-cyl.-watercooled Kubota diesel engine 37 kW = 50 hp
Tyres:	11.5/80-15.3 AS
Width:	1.020 mm-1.680 mm
Height with protection roof:	from 2.020 mm
Lifting height:	2.950 mm
Length incl. bucket:	4.185 mm
Turning radius:	1.100 mm
Operating weight:	2.800 kg
Lifting capacity:	2.000 kg
Tipping load, straight (pallet fork)*:	1.621 kg-1.739 kg
Tipping load, straight (bucket)*:	2.002 kg-2.191 kg
Speed:	0-20 km/h
Option:	0-28 km/h

* acc. to ISO 8313 (Boom horizontal)



As standard:

Low style loader, Combined oil cooler, Hydrostatic four wheel drive, HTF (High Traction Force), Genuine Schäffer axle, Multiple disk brake, maintenance free, Maintenance free articulated pendulum joint, Hydraulic quick gear 20 km/h switchable under load, Restraining system for protective roof, Adjustable steering column, Hour meter, rev counter, fuel and temperature gauge, 1 x LED headlamp front, Parallel lift, Third hydraulic function with control handle, Working hydraulics: 46 l/min, optional 52 l/min., Counter weight rear end, New headstock SWR with hydraulic tool lock.

Technical Specifications:

Engine:	4-cyl.-watercooled Kubota diesel engine 37 kW = 50 hp
Tyres:	11.5/80-15.3 AS
Width:	1.100 mm-1.680 mm
Height with protection roof:	2.270 mm
Height with cab:	2.220 mm
Lifting height:	3.250 mm
Length incl. bucket:	4.500 mm
Turning radius:	1.310 mm
Operating weight:	3.100 kg/cab 3.300 kg
Lifting capacity:	2.300 kg
Tipping load, straight (pallet fork)*:	1.783 kg-1.913 kg
Tipping load, straight (bucket)*:	2.010 kg-2.201 kg
Speed:	0-20 km/h
Option:	0-28 km/h

* acc. to ISO 8313 (Boom horizontal)



As standard:

Combined oil cooler, HTF (High Traction Force), hydrostatic four wheel drive, SPT (Schäffer Power Transmission), Genuine Schäffer axle, Multiple disk brake, maintenance free, Maintenance free articulated pendulum joint, Hydraulic quick gear 20 km/h switchable under load, Restraining system for protective roof, Adjustable steering column, Hour meter, rev counter, fuel and temperature gauge, Headlamp on protective roof version: 1 x LED on the boom; cabin version: 2 x front, 1 x rear, Parallel lift, Third hydraulic function with control handle, Working hydraulics: 52 l/min, optional 60 l/min., Counter weight rear end, Headstock SWH with hydraulic tool lock.

Technical Specifications:

Engine:	4-cyl.-watercooled Kubota diesel engine 37 kW = 50 hp
Tyres:	11.5/80-15.3 AS
Width:	1.230 mm-1.670 mm
Height with protection roof:	2.270 mm
Height with cab:	2.270 mm
Lifting height:	3.260 mm
Length incl. bucket:	4.730 mm
Turning radius:	1.450 mm
Operating weight:	3.400 kg/cab 3.520 kg
Lifting capacity:	2.400 kg
Tipping load, straight (pallet fork)*:	1.823 kg-2.149 kg
Tipping load, straight (bucket)*:	2.120 kg-2.428 kg
Speed:	0-20 km/h
Option:	0-28 km/h

* acc. to ISO 8313 (Boom horizontal)



As standard:

Combined oil cooler, Z-bar boom with parallel lift, Headstock type wheel loader with hydraulic tool lock, HTF (High Traction Force), hydrostatic four wheel drive, SPT (Schäffer Power Transmission), Genuine Schäffer planetary axles with limited slip differential, Multiple disk brake, maintenance free, Maintenance free articulated pendulum joint, Hydraulic quick gear 20 km/h switchable under load, Restraining system for protective roof, Adjustable steering column, Hour meter, rev counter, fuel and temperature gauge, Armrest right hand side, Headlamp on protective roof version: 1 x LED on the boom; cabin version: 2 x front, 1 x rear, Electric control of third hydraulic function at joystick, Working hydraulics: 68 l/min, Counter weight rear end.

Technical Specifications:

Engine	4-cyl.-watercooled Kubota diesel engine 37 kW = 50 hp
Tyres:	15.0/55-17 AS
Width:	1.540 mm-1.710 mm
Height with protection roof:	2.320 mm
Height with cab:	2.440 mm
Option:	2.320 mm
Lifting height:	3.400 mm
Length incl. bucket:	5.120 mm
Turning radius:	1.580 mm
Operating weight:	4.130 kg/4.280 kg
Lifting capacity:	2.800 kg
Tipping load, straight (pallet fork)*:	2.421 kg-2.519 kg
Tipping load, straight (bucket)*:	2.861 kg-3.002 kg
Speed:	0-20 km/h
* acc. to ISO 8313 (Boom horizontal)	



As standard:

HTF (High Traction Force), hydrostatic four wheel drive, SPT (Schäffer Power Transmission), Hydraulic quick gear 20 km/h switchable under load, Combined oil cooler, Z-bar boom with parallel lift, Working hydraulic 64 l/min, Headstock type wheel loader with hydraulic tool lock, Genuine Schäffer planetary axles with limited slip differentials, Rear pendulum axle, Maintenance free articulation joint, Multiple disk brake, maintenance free, Steering column adjustable, Hour meter, rev counter, fuel and temperature gauge, Electric control of third hydraulic function at joystick, Working hydraulics: 64 l/min, Adjustable armrest, Extra counter weight 220 kg, Counter weight rear end, Lighting system, Cyclone, 2 x headlamp front and 1 x rear.

Technical Specifications:

Engine:	4-cyl.-watercooled Deutz intercooler turbo diesel engine 55 kW = 75 hp
Tyres:	15.0/55-17 AS
Width:	1.540 mm-1.710 mm
Height with protection roof:	2.320 mm
Height with cab:	2.440 mm
Option:	2.320 mm
Lifting height:	3.400 mm
Length incl. bucket:	5.120 mm
Turning radius:	1.580 mm
Operating weight:	4.150 kg/cab 4.300 kg
Lifting capacity:	2.800 kg
Tipping load, straight (pallet fork)*:	2.463 kg-2.618 kg
Tipping load, straight (bucket)*:	2.901 kg-3.098 kg
Speed:	0-20 km/h
Option:	0-30 km/h

* acc. to ISO 8313 (Boom horizontal)

**As standard:**

Hydrostatic four wheel drive, HTF (High Traction Force), Hydraulic quick gear 20 km/h switchable under load, Combined oil cooler, Z-bar boom with parallel lift, Working hydraulic 64 l/min, Headstock type wheel loader with hydraulic tool lock, Genuine Schäffer planetary axles with limited slip differentials, Rear pendulum axle, Maintenance free articulation joint, Multiple disk brake, maintenance free, Steering column adjustable, Hour meter, rev counter, fuel and temperature gauge, Electric control of third hydraulic function at joystick, Working hydraulics: 64 l/min, optional 74 l/min., Adjustable armrest, Counter weight rear end, Lighting system, Cyclone, 2 x headlamp front and 1 x rear.

Technical Specifications:

Engine:	4-cyl.-watercooled Deutz intercooler turbo diesel engine 55 kW = 75 hp
Tyres:	15.5/60-18 AT
Width:	1.710 mm-1.900 mm
Height with SCV-cab:	2.530 mm
Option:	2.430 mm
Lifting height:	3.400 mm
Length incl. bucket:	5.450 mm
Turning radius:	1.750 mm
Operating weight with SCV-cab:	5.100 kg
Lifting capacity:	3.300 kg
Tipping load, straight (pallet fork)*:	3.325 kg-3.677 kg
Tipping load, straight (bucket)*:	3.751 kg-3.918 kg
Speed:	0-20 km/h
Option:	0-35 km/h

* acc. to ISO 8313 (Boom horizontal)



As standard:

Hydrostatic four wheel drive, HTF (High Traction Force), Hydraulic quick gear 20 km/h switchable under load, Combined oil cooler, hydraulic fan drive, Z-bar boom with parallel lift, Headstock type wheel loader with hydraulic tool lock, Planetary axles (Heavy Duty) with limited slip differentials; (8-hole), Rear pendulum axle, Maintenance free articulation joint, Multiple disk brake, maintenance free, Steering column adjustable in length and angle with SCV cab, Hour meter, rev counter, fuel and temperature gauge, Battery main switch, Electric control of third hydraulic function at joystick, Working hydraulics: 74 l/min, optional 88 l/min., Adjustable armrest, Counter weight rear end, Lighting system, Cyclone, 2 x headlamp front and 1 x rear.

Technical Specifications:

Engine:	4-cyl.-watercooled Deutz intercooler turbo diesel engine 75 kW = 102 hp
Tyres:	400/70-20 AS
Width:	1.750 mm-2.080 mm
Height with SCV-cab:	2.600 mm
Option:	2.500 mm
Lifting height:	3.400 mm/3.800 mm**
Length incl. bucket:	5.560 mm
Turning radius:	1.890 mm
Operating weight with SCV-cab:	5.550 kg/5.950 kg**
Lifting capacity:	4.200 kg
Tipping load, straight (pallet fork)*:	4.023 kg-4.198 kg
Tipping load, straight (bucket)*:	4.560 kg-4.623 kg
Speed:	0-20 km/h
Option:	0-35 km/h

* acc. to ISO 8313 (Boom horizontal)

** high lift version



As standard:

Hydrostatic four wheel drive, HTF (High Traction Force), Hydraulic quick gear 20 km/h switchable under load, Combined oil cooler, Z-bar boom with parallel lift, Headstock type wheel loader with hydraulic tool lock, Pressure free return, ZF planetary axles (Heavy Duty) with limited slip differentials, Rear pendulum axle, Maintenance free articulation joint, Multiple disk brake, maintenance free, SCV cab (Silence, Comfort, View), Steering column adjustable in length and angle, Hour meter, rev counter, fuel and temperature gauge, Battery main switch, Electric control of third hydraulic function at joystick, Adjustable armrest, Counter weight rear end, Lights, stronger gear pump, 105l, Cyclone, 2 x Headlamp front and 1 x rear.

Technical Specifications:

Engine:	4-cyl.-watercooled Kubota turbo-diesel engine 33 kW = 45 hp
Tyres:	10.0/75-15.3 AS
Width:	1.280 mm-1.570 mm
Height with protection roof:	2.215 mm
Height with cab:	2.110 mm
Lifting height:	3.750 mm
Length incl. bucket:	4.520 mm
Turning radius:	950 mm
Operating weight:	2.850 kg/cab 3.050 kg
Lifting capacity:	1.900 kg
Tipping load, straight*:	1.650 kg
Speed:	0-20 km/h
Option:	0-28 km/h

* Boom horizontal, not extended, with pallet fork (acc. to ISO 14397)



As standard:

Hydrostatic four wheel drive, HTF (High Traction Force), Hydraulic quick gear 20 km/h switchable under load, Combined oil cooler, Z-bar boom with hydraulic parallel lift, Ferro-Form sliders in telescopic boom, Crowd in cylinder placed in boom, Pressure relief of hydraulic couplings, Genuine Schäffer axle, Multiple disk brake, maintenance free, Maintenance free articulated pendulum joint, Restraining system for protective roof, Adjustable steering column, Hour meter, fuel control lamp and temperature gauge, Counter weight rear end, Counter weight 100 kg mounted under rear chassis, Water with anti freeze in tyres at rear axle, Wider fender (not detachable), Headlamp on protective roof version: 1 x LED on the boom; cabin version: 2 x front, 1 x rear, Third hydraulic function with control handle, Working hydraulics: 42 l/min, optional 51 l/min., Headstock SWH with hydraulic tool lock.

Technical Specifications:

Engine:	4-cyl.-watercooled Kubota turbo-diesel engine 33 kW = 45 hp
Tyres:	10.0/75-15.3 AS
Width:	1.280 mm-1.570 mm
Height with protection roof:	from 1.950 mm
Height with cab:	from 1.950 mm
Lifting height:	3.750 mm
Length incl. bucket:	4.580 mm
Turning radius:	980 mm
Operating weight:	2.900 kg/cab 2.975 kg
Lifting capacity:	1.900 kg
Tipping load, straight*:	1.650 kg
Speed:	0-20 km/h

* Boom horizontal, not extended, with pallet fork (acc. to ISO 14397)



As standard:

Low style loader, Hydrostatic four wheel drive, Hydraulic quick gear 20 km/h swit-
 chable under load, Combined oil cooler, Z-bar boom with hydraulic parallel lift,
 Ferro-Form sliders in telescopic boom, Crowd in cylinder placed in boom, Pressure
 relief of hydraulic couplings, Genuine Schäffer axle, Multiple disk brake, mainte-
 nance free, Maintenance free articulated pendulum joint, Restraining system for
 protective roof, Adjustable steering column, Hour meter, fuel control lamp and tem-
 perature gauge, Counter weight rear end, Counter weight 100 kg mounted under
 rear chassis, Water with anti freeze in tyres at rear axle, Wider fender (not detach-
 able), 1 x LED headlamp front, Third hydraulic function with control handle, Working
 hydraulics: 42 l/min, optional 51 l/min., Headstock SWH with hydraulic tool lock.

Technical Specifications:

Engine:	4-cyl.-watercooled Kubota diesel engine 37 kW = 50 hp
Tyres:	15.0/55-17 AS
Width:	1.420 mm-1.680 mm
Height with protection roof:	2.270 mm
Height with cab:	2.270 mm
Lifting height:	3.850 mm
Length incl. bucket:	4.835 mm
Turning radius:	1.230 mm
Operating weight:	3.700 kg/cab 3.900 kg
Lifting capacity:	1.950 kg
Tipping load, straight*:	1.710 kg
Speed:	0-20 km/h
Option:	0-28 km/h

* Boom horizontal, not extended, with pallet fork (acc. to ISO 14397)



As standard:

HTF (High Traction Force), hydrostatic four wheel drive, SPT (Schäffer Power Transmission), Hydraulic quick gear 20 km/h switchable under load, Combined oil cooler, Z-bar boom with hydraulic parallel lift, Ferro-Form sliders in telescopic boom, Crowd in cylinder placed in boom, Genuine Schäffer axles, Restraining system for protective roof, Multiple disk brake, maintenance free, Maintenance free articulation pendulum joint, Protective roof or cab, Adjustable steering column, Hour meter, rev counter, fuel and temperature gauge, Counter weight 110 kg mounted under rear chassis, Wide chassis, Water with anti freeze in tyres at rear axle, Headlamp on protective roof version: 1 x LED on the boom; cabin version: 2 x front, 1 x rear, Working hydraulics: 52 l/min, optional 60 l/min., Headstock type wheel loader with hydraulic tool lock.

Technical Specifications:

Engine:	4-cyl.-watercooled Kubota diesel engine 37 kW = 50 hp
Tyres:	15.0/55-17 AS
Width:	1.420 mm-1.680 mm
Height with protection roof:	from 2.020 mm
Lifting height:	3.850 mm
Length incl. bucket:	4.835 mm
Turning radius:	1.230 mm
Operating weight:	3.700 kg
Lifting capacity:	1.950 kg
Tipping load, straight*:	1.710 kg
Speed:	0-20 km/h
Option:	0-28 km/h

* Boom horizontal, not extended, with pallet fork (acc. to ISO 14397)



As standard:

Low style loader, Hydrostatic four wheel drive, HTF (high traction force), Hydraulic quick gear 20 km/h switchable under load, Combined oil cooler, Z-bar boom with hydraulic parallel lift, Ferro-Form sliders in telescopic boom, Crowd in cylinder placed in boom, Genuine Schäffer axles, Restraining system for protective roof, Multiple disk brake, maintenance free, Maintenance free articulation pendulum joint, Protective roof, Adjustable steering column, Hour meter, rev counter, fuel and temperature gauge, Counter weight rear end, Counter weight 110 kg mounted under rear chassis, Wide chassis, Water with anti freeze in tyres at rear axle, 1 x LED headlamp front, Working hydraulics: 52 l/min, optional 60 l/min., Headstock type wheel loader with hydraulic tool lock.

Technical Specifications:

Engine:	4-cyl.-watercooled Kubota diesel engine 37 kW = 50 hp
Tyres:	15.0/55-17 AS
Width:	1.540 mm-1.710 mm
Height with protection roof:	2.320 mm
Height with cab:	2.440 mm
Option:	2.320 mm
Lifting height:	4.250 mm
Length incl. bucket:	5.200 mm
Turning radius:	1.580 mm
Operating weight:	4.250 kg/cab 4.450 kg
Lifting capacity:	2.400 kg
Tipping load, straight*:	2.740 kg
Speed:	0-20 km/h

* Boom horizontal, not extended, with pallet fork (acc. to ISO 14397)



As standard:

HTF (High Traction Force), hydrostatic four wheel drive, SPT (Schäffer Power Transmission), Hydraulic quick gear 20 km/h switchable under load, Combined oil cooler, Z-bar boom with hydraulic parallel lift, Headstock type wheel loader with hydraulic tool lock, Ferro-Form sliders in telescopic boom, Crowd in cylinder placed in boom, Working hydraulic 64 l/min, Pressure free return, Pressure relief of hydraulic couplings, Genuine Schäffer planetary axles with limited slip differentials, Rear pendulum axle, Maintenance free articulation joint, Multiple disk brake, maintenance free, Steering column adjustable, Hour meter, rev counter, fuel and temperature gauge, Battery main switch, Electric control of third hydraulic function at joystick, Working hydraulics: 64 l/min, Adjustable armrest, Counter weight rear end, Lighting system, Cyclone, 2 x headlamp front and 1 x rear.

Technical Specifications:

Engine:	4-cyl.-watercooled Deutz intercooler turbo diesel engine 55 kW = 75 hp
Tyres:	15.0/55-17 AS
Width:	1.540 mm-1.710 mm
Height with protection roof:	2.320 mm
Height with cab:	2.440 mm
Option:	2.320 mm
Lifting height:	4.700 mm
Length incl. bucket:	5.200 mm
Turning radius:	1.580 mm
Operating weight:	4.300 kg/cab 4.500 kg
Lifting capacity:	2.400 kg
Tipping load, straight*:	2.800 kg
Speed:	0-20 km/h
Option:	0-30 km/h

* Boom horizontal, not extended, with pallet fork
(acc. to ISO 14397)



As standard:

Hydrostatic four wheel drive, HTF (High Traction Force), Hydraulic quick gear 20 km/h switchable under load, Combined oil cooler, Z-bar boom with hydraulic parallel lift, Headstock type wheel loader with hydraulic tool lock, Ferro-Form sliders in telescopic boom, Crowd in cylinder placed in boom, Working hydraulic 64 l/min, Pressure free return, Pressure relief of hydraulic couplings, Genuine Schäffer planetary axles with limited slip differentials, Rear pendulum axle, Maintenance free articulation joint, Multiple disk brake, maintenance free, Steering column adjustable, Hour meter, rev counter, fuel and temperature gauge, Battery main switch, Electric control of third hydraulic function at joystick, Working hydraulics: 64 l/min, optional 74 l/min., Adjustable armrest, Counter weight rear end, Lighting system, Cyclone, 2 x headlamp front and 1 x rear.

Technical Specifications:

Engine:	4-cyl.-watercooled Deutz intercooler turbo diesel engine 55 kW = 75 hp
Tyres:	15.5/60-18 AT
Width:	1.710 mm-1.900 mm
Height with canopy:	2.530 mm
Option:	2.430 mm
Lifting height:	4.900 mm
Length incl. bucket:	5.780 mm
Turning radius:	1.750 mm
Operating weight with SCV-cab:	5.600 kg-6.300 kg
Lifting capacity:	3.100 kg
Tipping load, straight*:	3.800 kg
Speed:	0-20 km/h
Option:	0-35 km/h

* Boom horizontal, not extended, with pallet fork
(acc. to ISO 14397)



As standard:

Hydrostatic four wheel drive, HTF (High Traction Force), Hydraulic quick gear 20 km/h switchable under load, Combined oil cooler, Hydraulic fan drive, Z-bar boom with hydraulic parallel lift, Headstock type wheel loader with hydraulic tool lock, Ferro-Form sliders in telescopic boom, Crowd in cylinder placed in boom, Working hydraulic 72 l/min, Pressure free return, Pressure relief of hydraulic couplings, Planetary axles (Heavy Duty) with limited slip differentials; (8-hole), Rear pendulum axle, Maintenance free articulation joint, Multiple disk brake, maintenance free, Steering column adjustable in length and angle with SCV cab, Hour meter, rev counter, fuel and temperature gauge, Battery main switch, Electric control of third hydraulic function at joystick, Working hydraulics: 74 l/min, optional 88 l/min., Adjustable armrest, Counter weight rear end, Lighting system, Cyclone, 2 x headlamp front and 1 x rear.

Technical Specifications:

Engine:	4-cyl.-watercooled Deutz intercooler turbo diesel engine 75 kW = 102 hp
Tyres:	400/70-20 AS
Width:	1.870 mm-2.080 mm
Height with SCV-cab:	2.600 mm
Option:	2.500 mm
Lifting height:	5.100 mm
Length incl. bucket:	6.040 mm
Turning radius:	2.240 mm
Operating weight with SCV-cab:	6.500 kg-7.550 kg
Lifting capacity:	3.800 kg
Tipping load, straight*:	4.500 kg
Speed:	0-20 km/h
Option:	0-35 km/h

* Boom horizontal, not extended, with pallet fork
(acc. to ISO 14397)



As standard:

Hydrostatic four wheel drive, HTF (High Traction Force), Hydraulic quick gear 20 km/h switchable under load, Combined oil cooler, Z-bar boom with hydraulic parallel lift, Headstock type wheel loader with hydraulic tool lock, Ferro-Form sliders in telescopic boom, Crowd in cylinder placed in boom, Pressure free return, Pressure relief of hydraulic couplings, ZF planetary axles (Heavy Duty) with limited slip differentials, Rear pendulum axle, Maintenance free articulation joint, Multiple disk brake, maintenance free, SCV-cab (Silence, Comfort, View), Steering column adjustable in length and angle with SCV cab, Hour meter, rev counter, fuel and temperature gauge, Battery main switch, Electric control of third hydraulic function at joystick, Adjustable armrest, Counter weight rear end, Lighting system, stronger gear pump, 105l, Cyclone, 2 x headlamp front and 1 x rear, telescopic cylinder with end cushioning.

Technical Specifications:

Engine:	4-cyl.-watercooled Deutz intercooler turbo diesel engine 100 kW = 136 hp
Tyres:	460/70-24 AS
Width:	2.320 mm-2.380 mm
Height with SCV-Plus-cab:	2.860 mm
Lifting height:	5.400 mm
Length incl. bucket:	6.260 mm
Turning radius:	2.280 mm
Operating weight with SCV-Plus-cab:	8.400 kg-9.700 kg
Lifting capacity:	4.200 kg
Tipping load, straight*:	5.350 kg
Speed:	0-20 km/h
Option:	0-40 km/h

* Boom horizontal, not extended, with pallet fork (acc. to ISO 14397)



As standard:

Hydrostatic four wheel drive, HTF (High Traction Force), Hydraulic quick gear 20 km/h switchable under load, Load-Sensing working hydraulics, 145 l/min., Flow sharing working hydraulics incl. proportional control of the telescopic arm, Electric control of standard hydraulic valve on joystick, Combined oil cooler, Z-bar boom with hydraulic parallel lift, Headstock type wheel loader with hydraulic tool lock, Ferro-Form sliders in telescopic boom, Crowd in cylinder placed in boom, Pressure free return, Electric pressure relief of hydraulic couplings, ZF planetary axles (Heavy Duty) with limited slip differentials, Rear pendulum axle, Maintenance free articulation joint, 2 steering cylinders, Multiple disk brake, maintenance free, SCV-Plus-Cabin (Silence, Comfort, View), Steering column adjustable in length and angle, Hour meter, rev counter, fuel and temperature gauge, engine monitoring, Battery main switch, Adjustable armrest, Counter weight rear end, Lights, Cyclone, 2 x headlamp front and 1 x rear, Hydraulic fan drive.

Technical Specifications:

Engine:	4-cyl.-watercooled Deutz intercooler turbo diesel engine 115 kW = 157 hp
Tyres:	500/70-24 AS
Width:	2.290 mm-2.490 mm
Height with SCV-cab:	2.970 mm
Lifting height:	6.100 mm
Length incl. bucket:	6.750 mm
Turning radius:	2.400 mm
Operating weight:	11.000 kg-13.000 kg
Lifting capacity:	5.300 kg
Tipping load, straight*:	7.900 kg
Speed:	0-30 km/h
Option:	0-40 km/h

* Boom horizontal, not extended, with pallet fork
(acc. to ISO 14397)



As standard:

Hydrostatic four wheel drive, HTF (High Traction Force), Hydraulic quick gear 20 or 30 km/h switchable under load, Load Sensing working hydraulics, 230 l/min, Flow sharing working hydraulics incl. proportional control of the telescopic arm, Combined oil cooler, Z-bar boom with hydraulic parallel lift, Headstock type wheel loader with hydraulic tool lock, Ferro-Form sliders in telescopic boom, Crowd in cylinder placed in boom, Pressure free return, Electric pressure relief of hydraulic couplings, Planetary axles HD with limited slip differentials, Rear pendulum axle, maintenance free articulation joint, 2 steering cylinders, Multiple disk brake, maintenance free, SCV-Plus-Cabin (Silence, Comfort, View), Steering column adjustable in length and angle, Hour meter, rev counter, fuel and temperature gauge, Battery main switch, Electric control of third hydraulic function at joystick, Adjustable armrest, Counter weight rear end, Lights, Water with anti freeze in tyres at rear axle, Cyclone, 2 x headlamp front and 1 x rear, Hydraulic fan drive.

4 IN 1 BUCKET



Width	Capacity	Bucket body
Compact Wheel Loader		
1,25 m	331 l	short
1,40 m	377 l	short
1,40 m	550 l	deep
1,65 m	637 l	deep
Wheel loader/Telehandlers		
1,40 m	550 l	deep
1,50 m	588 l	deep
1,65 m	647 l	deep
1,80 m	706 l	deep
2,00 m	661 l	deep
2,20 m	863 l	deep
2,40 m	942 l	deep

SOIL BUCKET WITH ANGULAR BODY



Width	Capacity	Width	Capacity
0,78 m	283 l	1,40 m	625 l
0,90 m	327 l	1,60 m	725 l
1,00 m	363 l	1,70 m	762 l
1,10 m	400 l	1,80 m	812 l
1,20 m	436 l	2,00 m	900 l
1,30 m	472 l	2,20 m	987 l
1,40 m	509 l	2,40 m	1057 l
1,50 m	545 l	2,50 m	1125 l
1,60 m	582 l		

SOIL BUCKET WITH ROUND BUCKET



Width	Capacity	Width	Capacity
0,78 m	302 l	1,30 m	503 l
0,90 m	348 l	1,40 m	542 l
1,00 m	387 l	1,50 m	581 l
1,10 m	426 l	1,60 m	620 l
1,20 m	465 l		

LIGHT MATERIAL BUCKET COMPACT WHEEL LOADER



Width	Capacity
0,78 m	400 l
0,90 m	461 l
1,00 m	513 l
1,20 m	615 l
1,30 m	666 l
1,40 m	718 l
1,50 m	769 l
1,60 m	820 l
1,80 m	923 l
2,00 m	1026 l

LIGHT MATERIAL BUCKET WHEEL LOADER/ TELEHANDLERS



Width	Capacity	Width	Capacity
1,40 m	890 l	2,40 m	1200 l
1,50 m	960 l	2,50 m	1536 l
1,60 m	1024 l	2,20 m high volume	2300 l
1,70 m	1088 l	2,40 m high volume	2500 l
1,80 m	1152 l	2,50 m high volume	3125 l
2,00 m	1280 l		
2,20 m	1408 l		

HIGH TIP BUCKET



Width	Capacity	Weight
1,20 m	700 l	335 kg
1,40 m	820 l	360 kg
1,60 m	940 l	385 kg
1,80 m	1040 l	500 kg
2,00 m	1160 l	535 kg
2,20 m	1280 l	570 kg

BUCKET WITH GRAB



Width	Capacity	Cylinder
0,78 m	330 l	1
0,90 m	380 l	1
1,00 m	420 l	1
1,20 m	500 l	1
1,40 m	590 l	2
1,60 m	670 l	2

GRAPPLE BUCKET



Width	Capacity	Weight
1,20 m	400 l	220 kg
1,30 m	433 l	230 kg
1,40 m	466 l	240 kg
1,50 m	500 l	250 kg
1,60 m	533 l	275 kg

MULTISHOVEL



Width	Capacity
1,35 m	500 l
1,60 m	900 l
1,40 m	750 l
1,60 m	900 l
1,80 m	1000 l
2,00 m	1100 l
2,20 m	1200 l
2,40 m	1300 l

MULTISHOVEL XL HEAVY DUTY



Width	Capacity
2,20 m	1800 l
2,40 m	2000 l

MANURE FORK WITH GRAB



Width	Cylinder	Tines
0,78 m	1	5
0,90 m	1	5
1,00 m	1	6
1,20 m	1	7
1,20 m	2	7
1,40 m	2	8

MANURE FORK WITH GRAB HEAVY DUTY



Width	Tines
1,20 m	7
1,40 m	8
1,60 m	9
1,80 m	10
2,00 m	11
2,40 m	13

MANURE FORK



Width	Tines	Tine length
0,78 m	5	800 mm
0,90 m	5	800 mm
1,00 m	6	800 mm
1,20 m	7	800 mm
1,40 m	8	800 mm
1,60 m	9	800 mm
1,70 m	10	1100 mm
1,90 m	11	1100 mm
2,10 m	12	1100 mm

SHEAR GRAB



Width	Capacity	Cylinder	Weight
Compact Wheel Loader			
0,95 m	600 l	2	450 kg
1,20 m	730 l	2	495 kg
1,40 m	870 l	2	540 kg
Wheel loader/Telehandlers			
1,60 m	1065 l	2	770 kg
1,80 m	1210 l	2	800 kg
2,00 m	1350 l	3	1040 kg
2,20 m	1495 l	3	1075 kg

DOZER BLADE



Width	Weight
1,50 m	150 kg
1,80 m	165 kg
2,00 m	335 kg
2,40 m	635 kg

SNOW BLADE



Width	Height	Working width 30° turned	Weight	Hydraulic turn
1,35 m	600 mm	1200 mm	265 kg	optional
1,50 m	600 mm	1340 mm	295 kg	optional
1,80 m	800 mm	1600 mm	352 kg	optional
2,10 m	800 mm	1870 mm	377 kg	standard
2,40 m	800 mm	2140 mm	402 kg	standard
2,70 m	800 mm	2410 mm	427 kg	standard

SNOW BLOWER



SPREADER



Capacity	Housing
120 l	2,5 mm stainless steel V4A
200 l	2,5 mm stainless steel V4A

MUCK BLADE



Width	Weight
1,50 m	110 kg
1,80 m	120 kg
2,10 m	130 kg
2,50 m	145 kg

FODDER BLADE



Design	Width
Onesided	0,75 m
Double-sided	1,50 m

HYDRAULIC RUBBER BLADE




Width	Width at 40°	Width folded	Weight
2,20 m	1,70 m	0,95 m	110 kg

BALE GRIPPER



Width	Bale size	Weight
1,00 m	0,90 m - 1,80 m	180 kg
1,80 m	1,00 m - 1,80 m	350 kg

UNWINDER FOR ROUND BALES




Weight	Tines	Tine length
250 kg	4	1,00 m

BIG BALE FORK



Width	Height	Tines	Weight
1,20 m	1,55 m	3	200 kg

PALETT FORK



Width	Tine length	Weight	Capacity
1,00 m	1,00 m	165 kg	2,5 t
1,00 m	1,20 m	185 kg	2,5 t
1,20 m	1,00 m	198 kg	3,5 t
1,20 m	1,20 m	215 kg	3,5 t

STRAW SPREADER



Width	Capacity	Width bucket edge	Weight
1,35 m	850 l	1,00 m	260 kg
1,55 m	1020 l	1,20 m	275 kg
1,75 m	1200 l	1,40 m	290 kg

BUCKET WITH MILLING HEAD



Width	Capacity
1,00 m	484 l
1,20 m	598 l
1,50 m	743 l

BUCKET FOR CONCENTRATES



Width	Capacity	Weight
1,20 m	475 l	210 kg
1,40 m	575 l	240 kg
1,60 m	675 l	300 kg

FEED BUCKET WITH CHAIN CONVEYOR



Model	Height	Width bucket edge	Overall width	Capacity	Weight
FD 100 KB	1200 mm	990 mm	1060 mm	780 l	260 kg
FD 120 KB	1200 mm	1190 mm	1240 mm	940 l	275 kg
FD 150 KB	1200 mm	1490 mm	1520 mm	1190 l	320 kg

Optional: Milling head and hydraulic control

SWEeper



Width	Sweep roller	Dirt tank	Weight
1,50 m	520 mm	no	260 kg
1,50 m	520 mm	yes	360 kg
1,80 m	520 mm	no	290 kg
1,80 m	520 mm	yes	390 kg
2,10 m	520 mm	no	310 kg
2,10 m	520 mm	yes	410 kg
2,30 m	520 mm	no	330 kg
2,30 m	520 mm	yes	430 kg

MOUNTED EXCAVATOR



Model	Weight	Width bucket	Max. reach	Max. height	Useable height	Working depth
For loader 2032 - 2345: NA 1200						
NA 1200	240 kg	200 mm	1750 mm	1700 mm	1300 mm	1200 mm
For loader 3545 - 4250: NA 1700						
NA 1700	390 kg	300 mm	2800 mm	2500 mm	1700 mm	2000 mm
For loader 4350 Z - 6680 Z - 6680 T: NA 2300						
NA 2300	550 kg	400 mm	2750 mm	2400 mm	1600 mm	2000 mm

POST HOLE DRILLER



Diameter	Oil needed	Weight
10 cm	20 l	125 kg
20 cm	20 l	140 kg
30 cm	20 l	152 kg
35 cm	20 l	164 kg
40 cm	20 l	176 kg

WORKING PLATFORM



Weight	Width	Depth	Height
225 kg	1,30 m	0,86 m	1,00 m

FLAIL MOWER



Model	Working width	Overall width	Oil-flow	Weight	Knives
MU-F Hydro 120	1,20 m	1,45 m	32 l/min	220 kg	20
MU-F Hydro 140	1,40 m	1,65 m	40 l/min	240 kg	24
MU-F Hydro 160	1,60 m	1,85 m	50 l/min	260 kg	28

FINISHING MOWER



Width	Weight
1,20 m	220 kg
1,50 m	280 kg
1,80 m	330 kg

SICKLE BAR MOWER



Width	Oil needed	Weight
1,50 m	20 l	195 kg
1,90 m	20 l	215 kg

ARENA LEVELER



Width	Suitable for
1,40 m	sand, textile shreds, fleece
1,60 m	sand, textile shreds, fleece

IMPORTERS

Australia

Agtech International
Cameron Moir
U5/71 Beringarra Rd
6090 Malaga-Perth
phone +61 1300882161
www.schaffer-loaders.com.au
office@schaffer-loaders.com.au

Austria

EZ AGRAR e.Gen.
Salzburger Str. 38
4020 Linz
phone +43 732 3472660
fax +43 732 34726640
www.ezagr.ar.at
office@ezagr.ar.at

Belarus

„Biocom Technology“ Ltd.
231741 Grodno region
Grodno district
Raista village, 15
phone +375 152937937
fax +375 152937937
www.biocomtechnology.by
info@biocomtechnology.by

Belgium

N. V. Heusdens Renting
Lichtenberglaan 1001
3800 St. Truiden
phone +32 11 683899
fax +32 11 683165
www.schaffer.be
info@schaffer.be

Bulgaria

Bulagro Mashini AD
Bulagro Center
Zheleznik District
6000 Stara Zagora
phone +35 9 885598389
fax +35 9 42600175
www.bulagro.com
rumen-savov@bulagro.com

Canada

Alberta
GMS Mechanical & Equipment Ltd.
311 23rd Street P.O. Box 1086
AB T0L 0Z0 Fort Macleod
phone +1 4035530000
fax +1 4035534600
www.gmsequip.com
erik@gmsequip.com

Manitaba

Schäffer Loaders Ltd.
653 Main Street North
Box 682, Morris
Manitaba R0G 1K0
phone +1 204 7462108
fax +1 204 7466806
bpi@mts.net

Ontario

Vandenburg Equipment
Service Ltd.
Eleventh Concession Road 159
N0E 1E0 Harley
phone +1 5198635719
fax +1 5198635719
www.vesontario.com
vesontario@gmail.com

Québec

Benco
2252 rang de la Savane, Richelieu
Québec J3L 6N8
phone +1 4506581802
fax +1 4506583103
www.benco.ca
administration@benco.ca

Czechia/Slovakia

Multos s. r. o.
K Silu 2263
39301 Pelhrimov
phone +420 565323284
fax +420 565327880
www.multos.cz
multos@iol.cz

Denmark/Sweden/Norway

Helms TMT-Centret A/S
Tavlundvej 4-6, Lind
7400 Herning
phone +45 99282930
fax +45 99282938
www.helmstmt.com
mail@helmstmt.com

Finnland

Turun Konekeskus Oy
Ruopankatu 8
20360 Turku
phone +358 207 459700
www.turunkonekeskus.fi
info@turunkonekeskus.fi

France

Ernest Roth Sàrl
16, Rue du Doubs
90101 Fêche-L'Eglise
phone +33 384549563
fax +33 384549564
www.ernestroth.com
loader@rothsa.com

Great Britain

Schäffer UK
Paul Gower
phone +44 7585452009
p.gower@schaeffer-loader.com
www.schafferuk.com

Greece

AGRIPAN S.A.
111 Orfeos Str.
11855 Athen
phone +302 103485000
fax +302 103461653
ekanima@agripan.gr

Iran

Shaver Car Loader Co.
110 Dr. Beheshti Ave.
3rd floor Apt 8
Teheran, Iran
phone +9821 884226345
fax +9821 88412522
www.schafferloader.ir
info@schafferloader.ir

Ireland/Scotland

Schäffer UK
Colin Gilbert
phone +44 7980715125
c.gilbert@schaeffer-loader.com
www.schafferuk.com

Island

Jötunn-Vélar hf
Austurvegur 69
800 Selfoss
phone +354 4800400
fax +354 4824108
www.jotunn.is
jotunn@jotunn.is

Israel

AGRO TAMIR TABOR LTD.
PO Box 126
Kfar Tabar-Industrial Zone
15241 Israel
phone +97 248718014
fax +97 245718015
liat@agrott.li

Italy

F. Staudacher
Fuggerstr. 18, Via Fugger
39049 Sterzing-Vipiteno
phone +39 0472 766010
fax +39 0472 766585
www.staudacher.it
info@staudacher.it

Kazakhstan

IP Kassenov A. ZH.
Company Optimal Kazakhstan
Egemen Kazakhstan st. 20-71
150000 Petropawlowsk
phone +770 14229173

**Lebanon/Syria/Jordan/Egypt/
Iraq/Nigeria**

Jerico Contracting & Trading Co.
Assad Badoui Bldg.
001 Main Street
Amioun, El Koura
Libanon
phone +961 3 231959
+961 7 0249000
fax +961 6 951818
www.jericolb.com
jericolb@hotmail.com

Lithuania

UAB "Dotnuva Baltic"
Parko g. 6, Akademija
58351 Kédainiai
phone +370 34737030
fax +370 34737040
www.dotnuvosprojektai.lt
gintaras.sprindziunas@dotnuvabaltic.lt

Luxembourg

Agri-Center S. A.
14, Nidderpallenerstrooss
8551 Noerdange
phone +352 23637501
fax +352 23637599
www.agri-center.lu
info@wowey.eu

Netherlands

Cees Berkhof
Barneveldsestraat 20
3927 CC Renswoude
phone +31 318572345
fax +31 318572325
www.ceesberkhof.nl
info@ceesberkhof.nl

Friesland/Groningen

Bromach
De Werf 1
Postbus 23
8401 JE Gorredijk
phone +31 513481070
fax +31 513481078
www.bromach.nl
info@bromach.nl

New Zealand

Glenbrook Machinery Ltd.
8 Nelson Street
PO Box 499
Pukekohe
2120 Auckland
phone +64 92386955
www.glenbrook.co.nz
phil@glenbrook.co.nz

Poland

Schaffer Ladowarki Pasek Sp. z. o. o.
ul. Lniana 1A
87-148 Lysomice
phone +48 566400057
fax +48 566400067
biuro@ladowarkipasek.pl

Romania

SC Farm Tech SRL
Calea Bucuresti, Nr. 115B
Sat Saftica, Comuna Balotesti
Judet Ilfov, Cod 077017
phone/fax +40 213529308
www.farmtech.ro
evabelle@xnet.ro
office@farmtech.ro

Russia

MTZ-Service Co Ltd
Elizarova pr. 38
Saint-Petersburg
phone +7 812 3272911
fax +7 812 5602282
www.mtz-service.ru
info@mtz.spb.ru

Smart-M LLC
Furazhniy prozed
Pos. 4, str. 2
Mytishchi City
Moscow regions
phone +7 495 6444902
fax +7 495 6444903
www.smart-m.ru
rogachev-smart@mail.ru
inanov-smart@mail.ru

PSSSPOK "AGRO+"
Oblast Nischnij Nowgorod
Bogorodski Rayon
d. Uschakowo
ul. Jubileinaja d. 6 of. 1
phone +7 8317045023
fax +7 8317045023
sasha-serednev@yandex.ru
kolganov_sergey@mail.ru

OOO TD „Evropeiskie Agrotehnologi Sibir“
Prozed Ujnyj 37A
656067 Barnaul
phone +7 3852722211
fax +7 3852722277
www.ea-sibir.ru
eat-sibir@yandex.ru

Slovenia

BrAU d.o.o.
Brezoviska cesta 9
1351 Brezovica pri Ljubljani
phone/fax +386 59039809
www.brau.si
info@brau.si

Spain/Portugal

FONDRIGO MAQUINARIA
Avenida de Galicia, 109
33770 Vegadeo, Asturias
phone/fax +34 985634238
info@fondrigomaquinaria.com

Switzerland

Ernest Roth S A
5, fbg St-Germain
2900 Porrentruy
phone +41 32 4657070
fax +41 32 4657071
www.rothsa.com
info@rothsa.com

Ukraine

PROFIAGRO LTD
Elektrykiv Str. 26
04176 Kiev
phone +38 0445220530
fax +38 0445999209
www.profiagro.com.ua
office@profiagro.com.ua

**United Arab Emirates/Oman/
Saudi Arabia/Qatar/Jemen**

Alzar F. Z. E.
LOB-21, G-01
P. B. No. 17311,
J. A. F. Z., Dubai,
United Arab Emirates
phone +97 14-8814928
fax +97 14-8814929
www.alzarfze.com
alzar@emirates.net.ae
info@alzarfze.com



made by **SCHÄFFER**

Technical data are subjects to change.
Stand 05/2017